



**Geometry**

	XXS	XS	S	M	L	XL
TTL length (virtual)	508	532	553	577	602	620
Head Angle	68.75	69.25	69.5	69.5	69.5	69.75
Seat Tube Angle	75	74.5	74.25	74	73.5	73.5
ST Length (C-C)	364	384	401	435	460	486
Chainstay Length	430	430	430	430	430	430
BB Drop	82	80	80	80	80	80
Fork Rake	45/51	45/51	45/51	45/51	45/51	45/51
Standover Height	700	735	765	791	810	833
Head Tube Length	90	115	136	158	174	194
Front Center	600	617	634	651	670	688
Wheelbase	1018	1028	1052	1069	1090	1106
Reach	362	375	386	402	417	429
Stack	540	564	585	605	620	640
Fork Length	425	425	425	425	425	425

**Technical Features**

<b>Construction</b>	One-piece, UD (uni-directional) carbon monocoque frame and fork
<b>Design</b>	All-road geometry with modular Flex-Fit system
<b>TT Slope</b>	Sloping, 15-21 degrees (size-specific)
<b>Seat Stays</b>	Twin, individual stays
<b>Tire Clearance</b>	32-50mm (measured)
<b>Seatpost</b>	31.6mm, round, 0mm or 25mm offset, replaceable external clamp
<b>Cabling</b>	Full internal routing, electronic drivetrain only
<b>Bottom Bracket</b>	T47, internal, 85.5mm width
<b>Drop Outs</b>	142mm thru-axle, UDH (Universal Derailleur Hanger) compatible, 140/160 rear rotors
<b>F. Derailleur</b>	Braze-on, removable, includes 1x blanking panel
<b>Standard Finish</b>	Nude, waxed carbon - Parlee Paintlab custom paint available
<b>Fork Specs</b>	Full carbon, integrated crown race, hidden cabling, flat mount disc, 100mm thru-axle, 160/180 rotor compatible – suspension fork ready geometry
<b>Headset</b>	Integrated IS52 upper and lower, stainless bearings
<b>Flex-Fit Spacers</b>	Included ENVE, FSA, and PRO short and tall top caps and universal fit cap