

## MVG Gel Series

- Perfect service battery for medium and large 12V and 24V systems
- Extremely long lifespan
- No gas formation with normal use
- Fast recharge, high charge current possible
- For intensive cycle use with a high number of charge/discharge cycles
- Very low self discharge
- High return on investment
- Two-year warranty



|                                  | MVG 12/25                      | MVG 12/55                         | MVG 12/85                       | MVG 12/120                        | MVG 12/140                        | MVG 12/200                         |
|----------------------------------|--------------------------------|-----------------------------------|---------------------------------|-----------------------------------|-----------------------------------|------------------------------------|
| <b>Part #</b>                    | <b>64000250</b>                | <b>64000550</b>                   | <b>64000850</b>                 | <b>64001200</b>                   | <b>64001400</b>                   | <b>64002000</b>                    |
| Nominal battery voltage          | 12V                            | 12V                               | 12V                             | 12V                               | 12V                               | 12V                                |
| Nominal battery capacity C20*    | 25 Ah                          | 55 Ah                             | 85 Ah                           | 120 Ah                            | 140 Ah                            | 200 Ah                             |
| Max charge current               | 12.5A                          | 27.5A                             | 42.5A                           | 60A                               | 70A                               | 100A                               |
| CCA to DIN                       | 110A                           | 230A                              | 270A                            | 450A                              | 540A                              | 630A                               |
| CCA to SAE                       | 175A                           | 380A                              | 450A                            | 760A                              | 920A                              | 1100A                              |
| Battery terminal                 | A-type                         | A-type                            | A-type                          | A-type                            | A-type                            | A-type                             |
| Max. outer Dimensions**<br>LxWxH | 6.6"x6.9"x5"<br>167x176x126 mm | 10.3"x5.4"x9.1"<br>261x136x230 mm | 13"x6.7"x9.3"<br>330x171x236 mm | 20.2"x7.4"x8.8"<br>513x189x223 mm | 20.2"x8.8"x8.8"<br>513x223x223 mm | 20.4"x10.8"x9.4"<br>518x274x238 mm |
| Weight                           | 21.2 lbs / 9.6 kg              | 41.9 lbs / 19 kg                  | 71.9 lbs / 32.6 kg              | 90.4 lbs / 41 kg                  | 108 lbs / 49 kg                   | 154.3 lbs / 70 kg                  |

\* C20 = battery capacity at a discharge time of 20 hours, till 10.5V per battery. \*\*Including terminals and grip handles

### Related Products



Battery Monitors  
page 91



Terminals & Covers  
page 67

