





PB 12e -14e -14e pro







The PB series was designed to give a professional solution for the specific requirements of the customer.

Lindhaus engineered this accessory like a machine, it is equipped with the most sophisticated technical features in the world.

Today the central vac, the canister vacuum and the back pack, can be equipped with the PB units, for an extraordinary increase in cleaning efficiency.



Long service life and low vibration levels, are achieved with superior engineering and precision manufacturing. All rotating components are balanced and protected by electronic controls.

ELECTRONIC LOGIC

Proven integrated circuits protect the motor and the transmission from overload and assist the operator in making the most efficient brush height

DESIGN SUPERIORITY

Rugged and efficient power brush picks up what others leave behind. Our maintenance free power brush has a three year warranty on the cogged drive belt. With non-marking rubber tires and an electrical switch position to stop the power brush motor, the transition to hard floor saves time and reduces airborne dust.

DRY CLEANING SYSTEM (Standard on PB12e - 14e)

The PB12e and PB14e have the built in Lindhaus patented Dry Cleaning System; a perfect solution to clean and sanitize carpets and rugs with no risk and minimal effort. It scrubs the Lindhaus compound until it penetrates into the fibers reducing bacteria and dust mites. A short wait of 20 min. to let the compound to dry and it can be sucked with the same power nozzle.

PB14e pro PROFESSIONAL FOR HEAVY DUTY APPLICATIONS

This professional heavy duty power nozzle is equipped with stainless steel shoe plate, tool free quick brush side exchange, side cylinders for easy shut off, motor soft start and maintain the brush constant speed.



along wall cleaning, rear door for easy replacement of the motor protection filter, a more sophisticate electronic logic which control the overload, motor



TECHNICAL DATA	PB 12e	PB 14e	PB 14e pro
Input power (W)	150	150	150
Electronic overload control	standard	standard	standard
Electric speed control	N/A	N/A	standard
LED version	optional	optional	N/A
Cogged drive belt	standard	standard	standard
Brush speed (RPM)	5000	5000	5000
Brush height adjustement	standard	standard	standard
Quick brush replacement no tools	standard	standard	standard
Dry Cleaning System	standard	standard	N/A
Brush width mm/(in.)	270/(10,5")	350/(13,75")	350/(13,75")
Suction width mm/(in.)	300/(12")	380/(15")	383/(15")
Double insulation	standard	standard	standard













