According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS Number: SKGB4x1

G.O.P Grease, Oil, Paint Remover

Revision Date: 12/1/2019

Page 1 **of** 6

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

1

Soklene supply 600 s Andreasen Drive suite F Escondido Ca 92029

INFOTRAC: 1-800-535-5053 Emergency: Phone: 760 2945582 Fax: (858) 729-4888 Email: info@soklenesupply.com> Web: soklenesupply.com >



Product Name: Revision Date:	G.O.P. Grease, Oil, Paint Remover 12/1/2019
Product Code:	GCS-2577
Chemical Formula:	Proprietary
Product Use:	Cleaner

2

HAZARDS IDENTIFICATION

Health hazards:	Acute toxicity, Oral	Category 4
	Serious eye damage	Category 2B
	Skin corrosion	Category3
	Acute toxicity/ Inhalation	Category 4

Environmental hazards: Not classified. **OSHA** defined hazards: Not listed. Label elements

Signal Word: WARNING

Hazard Statements:

H302 Harmful if swallowed. H320 Cause eye Irritation H316 Cause mild skin irritation. H332 Harmful If Inhaled

Precautionary Statements:

Prevention:

Do not breathe dusts or mists. Wash hands and exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response:

Call a POISON CENTER/doctor/medical professional if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor/medical professional. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable breathing. Immediately call a POISON CENTER/doctor/medical professional. Specific treatment (see Section 4 on the Safety Data Sheet). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC) None. Supplemental information None.



According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS Number:

3

4

G.O.P Grease, Oil, Paint Remover

Revision Date: 12/1/2019

Page 2 of 6

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS number	Less Than%
Solvent	64742-47-8	80.0000
2-Butoxyethanol	111-76-2	30.0000

Other components below reportable levels

FIRST AID MEASURES

Inhalation:	Move to fresh air. Call a physician if symptoms develop or persist.
Skin Contact:	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye Contact:	Rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention. Eye wash stations should be located in work area.
Ingestion:	Rinse mouth. Get medical attention if symptoms occur. Do not induce vomiting.
Most important symptoms/effects, acute and delayed	Dermatitis. Rash. May cause an allergic skin reaction.
Indication of immediate	Provide general support measures and treat symptomatically. Keep victim under observation.
medical attention and special treatment needed	Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5

FIRE FIGHTING MEASURES

Suitable extinguishing media: Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2) None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Wear appropriate protective equipment and clothing during clean-up. Wear eye/face protection.
Methods and materials for containment and cleaning up	Caution – spillages may be slippery.
	Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.
	Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS Number:

G.O.P Grease, Oil, Paint Remover

Revision Date: 12/1/2019

```
Page 3 of 6
```

Never return spills to original container for re-use. For waste disposal, see section 13 of the SDS.

Species

Sampling Time

Handling Precautions:

utions:Do not release into the environment (see section 12). Avoid discharge into areas not
consistent with package labeling.

 7
 HANDLING AND STORAGE

 Precautions for safe handling:
 Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Store in original tightly closed container. Do not store in extreme conditions.

including any incompatibilities

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

Components

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Value

Components	Туре	Value
	PEL	1 ppm
US ACGIH Threshold Limit Values		
Components	Туре	Value
Solvent	STEL	152 ppm
2-Butoxyethanol	STEL	20 ppm
Biological limit values ACGIH Biological Exposure Indice	95	

Determinant

Componente	Value	Dotorminant	opeolog	Sumpling Time	
Appropriate engineering controls: Individual protection measures	mechanical ven	tilation.		y accessible. Provide natural or	
Eye/face protection	Avoid contact w	ith eyes. Wear safety glass	ses with side shield	ls (or goggles).	
Skin protection Hand protection Other		te chemical resistant glove ve shirts with pants.	S.		
Respiratory protection Thermal hazards General hygiene	Wear appropriat	ection not required. te thermal protective clothin te thermal protective clothin	0		
considerations	smoking. Routin	0 0	d protective equipn	efore eating, drinking, and/or nent to remove contaminants. workplace.	

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	
Physical State	Liquid.
Color	Clear
Odor	Solvent.
Odor threshold	N/E.

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

G.O.P Grease, Oil, Paint Remover

Revision Date: 12/1/2019

Page 4 of 6

pH Melting/freezing point Initial boiling point and boiling range Evaporation rate Flammability Flammability Limits Upper
Lower
Vapor pressure
Vapor density
Specific gravity (water=1)
Solubility in water
Partition coefficient
(n-octanol/water)
Auto-ignition temperature
Decomposition temperature
Volatile

N/E. Flash point N/E. @115' F TCC. Not available. Not available. Not available. .84 Complete. Not available. Not available.

N/E 100%.

10

SDS Number:

STABILITY AND REACTIVITY

Reactivity Chemical stability	Material is stable under normal conditions. Material is stable under normal conditions.
Possibility of hazardous reactions	None Known
Conditions to avoid Incompatible materials Hazardous decomposition	None Known Strong acids, or strong oxidizing agents.
products	Material does not decompose at ambient temperatures.

11

TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	
Ingestion	Corrosive to mucous membranes.
Inhalation	Minimally Toxic based on test data for structurally similar materials
Skin contact	None Expected.
Eye contact	Irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Acute toxicity

May be harmful if swallowed.

Compent	Route and Species	LD50
Solvent	Oral,	15,000 mg/kg estimated
2-Butoxyethanol	Oral, Rat	470 mg/kg estimated

*Estimates for product may be based on additional component data not shown

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS Number:

G.O.P Grease, Oil, Paint Remover

Revision Date: 12/1/2019

Page 5 of 6

Serious eye damage/ irritation		
Respiratory sensitization	Not classified.	
Skin sensitization	Not classified.	
Germ cell mutagenicity	Not classified.	
Carcinogenicity	Not considered a carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not Listed.		
Reproductive toxicity	Not classified.	
Specific target organ toxicity		
 single exposure 	Not classified.	
Specific target organ toxicity		
 repeated exposure 	Not classified.	

Aspiration hazard

12

ECOLOGICAL INFORMATION

Component	Species	Test Results
2-Butoxyethanol	Daphnia.	EC50 (24hr) 1818 mg/L.

*Estimates for product may be based on additional component data not shown

Persistence and degradability	No data available.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No data available.

13	DISPOSAL CONSIDERATIONS		
Disposal instructions		Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/internatio nal regulations. Do not release to the environment.	
Local disposal regulations Waste from residues/unused product		Dispose in accordance with all applicable regulations Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. (See: Disposal instructions).	
Contaminated packaging		Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may contain product residue, follow label warnings even after container is emptied.	

14 TRANSPORT INFORMATION

DOT	
UN number	N/A
Shipping name	ORM-D
Technical Name	Consumer Commodity
Hazard Class	8
Subsidiary risk	
Packaging group	III
Marine pollutant	

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Read safety instructions, SDS, and emergency procedures before handling.

SDS Number:

15

G.O.P Grease, Oil, Paint Remover

Revision Date: 12/1/2019

Page 6 of 6

Special precautions for user Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code DOT

REGULATORY INFORMATION

US federal regulations

SARA 302 Extremely hazardous substance Not listed. SARA 304 Emergency release notification Not listed. SARA 311/312 Hazard Categories 2-Butoxyethanol CAS No. 111-76-2 % Less Than 30.0000.

SARA 313 (TRI reporting) California Prop 65 Surfactant 68987-81-5 Less Than 1.0000

16 OTHER INFORMATION Issue date 02/24/2015 **Revision date** 04/23/2015 Version # 1.0010 **HMIS®** ratings Health: 2 Flammability: 0 Physical hazard: 0 **NFPA** ratings Health: 2 Flammability: 0 Instability: 0 Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowled ge, and have been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by the text. **Revision information** First issue.