

Deckcote

Technical Information

Timber & Deck Finish

THE PRODUCT

Painted Earth Deckcote consists of a blend of selected oils and additives designed to replenish and protect your precious timber substrates.

The oils penetrate deeply into the timber, enriching and revitalizing whilst allowing the timber to breathe naturally.

The selected additives work 2 fold by absorbing harmful UV radiation to protect the timber from premature graying and also protecting the timber from a range fungal and algae attack.

ADVANTAGES

- *excellent durability*
- *deep penetration into the timber*
- *fast drying*
- *does not crack, peel or chip*
- *allows the timber to breathe*
- *UV blockers added*
- *fungus and mould resistant formulation*
- *easy recoating*
- *very low odour*
- *contains natural oils*
- *developed for Australian conditions*
- *easy wash up in water*

TECHNICAL DATA

gloss level:	low sheen
specific gravity:	1.01 - 1.03
solids :	23% weight
VOC: approx.	0.9% (40g/L)
Usage:	10 – 18m ² /litre
touch dry:	30 – 60 minutes*
re-coat :	4 hours*
through dry	5 days*

*depending upon relative humidity, air circulation, temperature and film thickness when recoated by itself

APPLICATION PROCEDURE

The substrate must be clean, free of dust, oil and silicone.

This product can be applied by brush, pad applicator or spray system.

2 – 3 coats are necessary for optimum protection.

Apply the product along the length of the boards including the edges and end grain.

Allow to dry for 3 hours before applying the second coat

COMMENTS

Do not allow to rain on within 12 hours of last application