



**OM-D E-M1 Mark III**



**OM-D E-M1 Mark II**

|   |   |   |
|---|---|---|
| <b>Sensor</b>   | 20 MP Live MOS Sensor   |   |
| <b>Image Processor</b>                                  | TruePic™ IX   | TruePic™ VIII   |
| <b>AF Points</b>  | 121-point All Cross Type Phase + Contrast Detection   |   |
| <b>AF Point Control</b>                                 | Joystick Control with Vertical, Horizontal and Diagonal Movement  | Four Way Control Button with Vertical and Horizontal Movement |
| <b>Center Start / Center Weighted AF</b>                | Yes   |   |
| <b>Starry Sky AF</b>                                    | Yes   | No  |
| <b>Image Stabilization</b>                              | 5-Axis<br>Up to 7.5 Shutter Speed Steps Compensation  | 5-Axis<br>Up to 6.5 Shutter Speed Steps Compensation          |
| <b>ISO Range</b>  | ISO L64, L100<br>200 - 25,600   | ISO L64<br>200 - 25,600                                       |
| <b>ISO Auto Range</b>                                   | ISO 200 to 6400   |   |
| <b>Max Shutter Speed</b>                                | Mechanical: 1/8000 to 60 sec<br>Electronic: 1/32000 to 30 sec   |   |
| <b>Sequential Shooting Speed</b>                        | Up to 15 fps (S-AF), 10 fps (C-AF) Mechanical Shutter<br>Up to 60 fps (S-AF), 18 fps (C-AF) Silent Electronic Shutter |   |
| <b>EVF<br/>(Electronic Viewfinder)</b>                  | 2.36M dot Progressive Scan LCD Electronic Viewfinder<br>0.74x Magnification (35mm Equivalent)                         |   |
| <b>Rear Monitor</b>                                     | 3.0-inch Vari-angle Touch LCD, approx. 1.04 million dots (3:2)  |   |
| <b>High Res Shot Mode</b>                               | Handheld 50MP JPEG<br>Tripod 80MP JPEG  | Tripod 50MP JPEG  |
| <b>Live ND*<br/>(Electronic Neutral Density Filter)</b> | Yes<br>(ND 2, 4, 8, 16, 32)   | No  |
| <b>Anti-Flicker Shooting Mode</b>                       | Yes   |   |
| <b>4K Video</b>   | 4K 24/30P<br>OM-Log Mode + LUT File for DaVinci Resolve   |   |
| <b>Accessory Vertical Grip / Power Battery Holder</b>   | Yes (HLD-9)   |   |
| <b>Customizable MyMenu</b>                              | Save up to 35 functions for quick access<br>(5 tabs maximum of 7 items each)  | No  |
| <b>Interval Shooting</b>                                | Max of 9,999 frames   | Max of 999 frames   |
| <b>Weathersealed</b>                                    | Dust-proof, Splash-proof (IPX1 Certified), Freezeproof to 14°F (-10°C)  |   |
| <b>Firmware Update via Smartphone with OI.Share App</b> | Yes   | No  |
| <b>Wi-Fi Connectivity</b>                               | Built-in (IEEE 802.11a/b/g/n)   |   |
| <b>Bluetooth LE Connectivity</b>                        | Instantly pairs with your smart device and transfer images even when powered off                                      | No  |
| <b>SD Card Compatibility</b>                            | Dual Card Slots (Slot 1 UHS-II Compatible)  |   |
| <b>USB Interface</b>                                    | USB 3.0 Type-C with USB PD Charging<br>(USB charger not included)   | USB 3.0 Type-C  |
| <b>Battery Life</b>                                     | Approx. 420 Shots   | Approx 450 Shots  |
| <b>Shutter Durability</b>                               | 400,000 actuations (mechanical)   | 200,000 actuations (mechanical)                               |
| <b>Dimensions *CIPA compliant</b>                       | 134.1 (W) x 90.9 (H) x 68.9 (D)   |   |
| <b>Weight *CIPA compliant</b>                           | Approx. 580 g   | Approx. 574 g   |
| <b>Battery</b>  | BLH-1   |   |