

<b>MODEL NAME</b>	FUJIFILM X-T4
<b>Number of effective pixels</b>	26.1 million pixels
<b>Image sensor</b>	23.5mm×15.6mm (APS-C) X-Trans CMOS 4 with primary color filter.
<b>Storage media</b>	SD memory card (~2GB) / SDHC memory card (~32GB) / SDXC memory card (~512GB) UHS-I / UHS-II / Video Speed Class V90 *1
<b>File format of still image</b>	JPEG: Exif Ver.2.3 *2 : RAW: 14bit RAW (RAF original format) TIFF: 8/16bit RGB
<b>Lens mount</b>	FUJIFILM X Mount
<b>Sensitivity</b> <b>Standard output</b> <b>Extended output</b>	AUTO1 / AUTO2 / AUTO3 (up to ISO12800) / ISO160 to 12800(1/3 step) ISO80 / 100 / 125 / 25600 / 51200
<b>Exposure control</b>	TTL 256-zone metering, Multi / Spot / Average / Center Weighted
<b>Exposure mode</b>	P (Program AE) / A (Aperture Priority AE) / S (Shutter Speed Priority AE) / M (Manual Exposure)
<b>Exposure compensation</b>	-5.0EV~+5.0EV 1/3EV step (Movie: -2.0EV~+2.0EV)
<b>Image stabilizer</b> <b>Mechanism</b> <b>Compensation Effect</b> <b>Digital Image Stabilization</b> <b>IS MODE BOOST</b>	Image sensor shift mechanism with 5-axis compensation Maximum 6.5 stops (based on CIPA standard. Pitch/yaw shake only.) Yes (movie mode only) Yes (movie mode only)
<b>Shutter type</b>	Focal Plane Shutter
<b>Movie recording</b> <b>File format</b> <b>File size</b> <b>Frame rate</b> <b>Recording time</b>	MOV (MPEG-4 AVC/H.264, HEVC/H.265, Audio: Linear PCM / Stereo sound 24bit / 48kHz sampling) MP4 (MPEG-4 AVC/H.264, Audio: AAC) All Intra/Long-GOP * All Intra can be used with following settings. DCI4K/4K 29.97p/25p/24p/23.98p 400Mbps Full HD 2048×1080 / Full HD 1920×1080 / 59.94p/50p/29.97p/25p/24p/23.98p 200Mbps DCI 4K 4096×2160 / 59.94p/50p/29.97p/25p/24p/23.98p / 400Mbps/200Mbps/100Mbps 59.94p/50p: up to approx. 20min. 29.97p/25p/24p/23.98p: up to approx. 30min 4K 3840×2160 / 59.94p/50p/29.97p/25p/24p/23.98p / 400Mbps/200Mbps/100Mbps 59.94p/50p: up to approx. 20min. 29.97p/25p/24p/23.98p: up to approx. 30min Full HD 2048 ×1080 / 59.94p/50p/29.97p/25p/24p/23.98p / 200Mbps/100Mbps/50Mbps up to approx. 30min. Full HD 1920×1080 / 59.94p/50p/29.97p/25p/24p/23.98p / 200Mbps/100Mbps/50Mbps up to approx. 30min. Full HD 1920×1080) High speed rec.] 240p / 200p 200Mbps(recording) up to approx. 3min. 120p / 100p 200Mbps(recording) up to approx. 6min. *For recording movies, use a SD memory card with UHS Speed Class 3 or higher. *For recording movies in 400Mbps, use a SD memory card with Video Speed Class 60 or higher. *Recording movies in 400Mbps can be done with DCI4K/4K 29.97p/25p/24p/23.98p. *DCI4K 59.94p/50p is not available when H.264 is selected. *Although movie recording will continue without interruption when the file size reaches 4GB, subsequent footage will be recorded to a separate file which must be viewed separately.
<b>Flash modes</b> <b>Sync. Mode</b> <b>Flash Mode</b>	1ST CURTAIN / 2ND CURTAIN / AUTO FP(HSS) (excl. EF-X8) TTL (TTL AUTO (P mode) / STANDARD / SLOW SYNC. ) / MANUAL / COMMANDER / OFF (When EF-X8 is set) TTL (TTL AUTO (P mode) / STANDARD / SLOW SYNC. ) / MANUAL / MULTI / OFF (When SHOE MOUNT FLASH is set)
<b>LCD monitor</b>	3.0 inch, aspect ratio 3:2, approx. 1.62 millions dots touch screen color LCD monitor(approx. 100% coverage)
<b>Viewfinder</b>	0.5 inch approx. 3.69 millions dots OLED Color Viewfinder / Coverage of viewing area vs. capturing area: approx. 100% Eyepoint: approx. 23mm (from the eyepiece lens) Diopter adjustment: -4~+2m-1 (lockable) Magnification: 0.75× with 50mm lens (35mm equivalent) at infinity and diopter set to -1m-1 Diagonal angle of view: approx. 38° (Horizontal angle of view: approx. 30° ) Built-in eye sensor
<b>Terminal</b> <b>Digital interface</b> <b>HDMI output</b> <b>Other</b>	USB Type-C (USB3.2 Gen1x1) HDMI micro connector (Type D) ø3.5mm, stereo mini connector (Microphone) / ø2.5mm, Remote Release Connector, Hot shoe, Synchronized terminal
<b>Dimensions</b>	(W) 134.6mm × (H) 92.8mm × (D) 63.8mm (minimum depth 37.9mm)
<b>Weight</b>	Approx. 607g (including battery and SD memory card) Approx. 526g (excluding battery and SD memory card)

\*1 Please see the Fujifilm website to check SD memory card compatibility.

\*2 Exif 2.3 is a digital camera file format that contains a variety of shooting information for optimal printing.