Compatible applications: 2011-2016 Ford F-150 5.0L Coyote 2011-2016 Ford F-150 EcoBoost 2011-2017 Ford Mustang 5.0L Coyote 2015-2019 Ford Mustang 2.3L EcoBoost 2015-2017 Ford Mustang V6



Dakota Digital Ford Oil Pressure Adapter

1/4-18 NPTF



1/4-18 NPTF

1/8-27 NPTF

1. Begin installation by locating and removing the factory oil pressure sensor. This sensor requires a 13/16" deep socket wrench.



2. Wrap adapter threads with quality thread tape. Then, thread oil pressure adapter into the oil pressure port on the engine. Tighten adapter using a ¾" open end wrench. Ensure the adapter oil pressure port is facing the direction that is accessible.



3. Wrap the factory oil pressure sensor threads with quality thread tape. Thread the sensor into the end of the oil pressure adapter using a 13/16" deep socket wrench. Plug the factory oil pressure connector back into the sensor.



- 4. Wrap the aftermarket oil pressure sensor threads with quality thread tape. Thread the sensor into the side of the oil pressure adapter using the appropriate wrench for the aftermarket sensor.
- 5. Route the aftermarket oil pressure harness to the sensor. Route the other end of this harness to the instrument system. Secure harness using zip ties ensuring to keep harness away from hot areas.



MARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North Sioux Falls, SD 57107

www.dakotadigital.com dakotasupport@dakotadigital.com Phone (605) 332-6513 Fax (605) 339-4106

© Copyright 2020 - Dakota Digital