

70 Gram Silt Fence Fabric Specifications



Property:	Test Procedures:	American Standard:
Style		70 gsm
Weave		11x11 Weave
Grab Tensile	ASTM D 4632	114
Grab Elongation	ASTM D 4632	27%
Mullen Burst	ASTM D 3786	205 psi
CBR Puncture	ASTM D 4833	50 lbs.
Trapezoid Tear	ASTM D 4533	52 lbs.
Apparent Opening Size	ASTM D 4751	40 Sieve
Permittivity	ASTM D 4491	0.05 Sec
UV Resistance	ASTM D 4355	80% @ 500 hrs.
Flow Rate	ASTM D 4491	24.2 gal/min/ft
Roll Width		3 ft. (36 inches)

DISCLAIMER: Description regarding the products described herein are based solely upon information provided by the manufacturer and are provided for information purposes only. NOTHING CONTAINED HEREIN SHOULD BE CONSTRUED AS CREATING AN EXPRESSED OR IMPLIED WARRANTY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS, EACH OF WHICH IS HEREBY DISCLAIMED. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The final determination as to the suitability of any product, in any application, rests solely with the user.



Partnering To Protect Our Environment

Silt Management Supplies, LLC.
Phone: 281-717-8921
www.siltmanagementsupplies.com