



Partnering To Protect Our Environment

**20439 Westfield Commerce Drive
Katy, Texas 77449-2569
Phone: 281-717-8921
www.siltmanagementsupplies.com**

Description: 70 Gram Silt Fence Fabric w/ 14-gauge 4x4 Wire

*Disclaimer: Description regarding the products described herein are based solely upon information provided by the manufacturer and are provided for information purposes only. **Nothing contained herein should be construed as creating an expressed or implied warranty, including warranties of merchantability and fitness, each of which is hereby disclaimed. There are no warranties that extend beyond the description on the face hereof. The final determination as to the suitability of any product of Silt Management Supplies, LLC. in any application rests solely with the user. Silt Management Supplies, LLC. reserves the right to alter or modify its products and descriptions at any time without notice.***

Product Type: 70-Gram Silt Fence Material Polymer: Polypropylene

PROPERTY	TEST PROCEDURES	AMERICAN STANDARD
Style		70 Gsm
Weave		11x11 Weave
Grab Tensile	ASTM D 4632	114
Mullen Elongation	ASTM D 4632	27%
Mullen Burst	ASTM D 3786	205 psi
CBR Puncture	ASTM D-4833	50 lbs.
Trapezoidal Tear	ASTM D-4533	52 lbs.
Apparent Opening Size (AOS)	ASTM D-4751	40 Sieve
Permittivity	ASTM D-4491	0.05 Sec
UV Resistance	ASTM D-4355	80% @ 500 hrs.
Water Flow	ASTM D-4491	24.2 gal/min/ft ²
Roll Width		3 ft

Product Type: 14-Gauge 4" x 4" Wire

PROPERTY	AMERICAN STANDARD
Height	24 in
Wire Space	4" x 4"
Top/Bottom Wires	14-gauge

<i>Vertical/Horizontal Filler Wires</i>	<i>14-gauge</i>
<i>Zinc Coating</i>	<i>Commercial Class</i>
<i>Roll Length</i>	<i>100 ft.</i>

Manufactured & tested by: L&M Supply Co., Inc.

Unless otherwise noted, this certification is based on testing conducted by our quality assurance & quality control testing laboratories at the time of manufacturing. L&M Supply Co, Inc. issued this letter of certification to indicate their commitment in providing customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

*Respectfully,
Silt Management Supplies, LLC.*