



Partnering To Protect Our Environment

20439 Westfield Commerce Drive
Katy, Texas 77449-2569
Ph. 281-717-8921
Email: sms@siltmanagementsupplies.com
www.siltmanagementsupplies.com

Subject: LM 800

This letter certifies that our LM 800, Non-woven filter fabric, meets the requirements for non-woven geotextile fabric. The average laboratory test values are as follows:

PROPERTY	TEST METHOD	UNIT	ROLL VALUE
Tensile Strength	ASTM D 4632	Lbs	205
Elongation	ASTM D 4632	%	50
Trapezoidal Tear	ASTM D 4533	Lbs	85
CBR Puncture Strength	ASTM D 6241	Lbs	535
AOS	ASTM D 4751	Sieve	80
Permittivity	ASTM D 4491	Sec-1	1.35
Water Flow Rate	ASTM D 4491	Gpm/ft	90
UV Resistance	ASTM D 4355	%/hours	70/500

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing.

This letter of certification was issued to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Manufactured by L&M Supply Co.

Visit: www.siltmanagementsupplies.com