

Silt Management Supplies, LLC.  
 20439 Westfield Commerce Drive  
 Katy, Texas 77449-2569  
 Phone: 281-717-8921  
 Email: [sms@siltmanagementsupplies.com](mailto:sms@siltmanagementsupplies.com)  
[www.siltmanagementsupplies.com](http://www.siltmanagementsupplies.com)

# 70 Gram Fabric w/ 14G 2"x4" Wire

## 70 Gram Silt Fence Fabric w/ 14G 2x4 Wire

Product Type: LM 70 Gram Silt Fence  
 Polymer: Polypropylene

Property	Test Procedures	American Standard
• Style		70 Gsm
• Weave		11x11Weave
• Grab Tensile	ASTM D 4632	114
• Grab Elongation	ASTM D 4632	27%
• Mullen Burst	ASTM D 3786	205 psi
• CBR Puncture	ASTM D 4833	50 lbs
• Trapezoid Tear	ASTM D 4533	52 lbs
• Apparent Opening Size	ASTM D 4751	40 Sieve
• Permittivity	ASTM D 4491	0.05 Sec
• UV Resistance	ASTM D 4355	80% @ 500 hrs
• Water Flow	ASTM D 4491	24.2 gal/min/ft <sup>2</sup>
• Roll Width		3 ft

Product Type: 14 Gauge 2"x4" Wire

Property	Test Procedures	American Standard
• Height		24 in
• Wire Space		2" x 4"
• Top/Bottom Wires		14 gauge
• Vertical/Horizontal Filler Wires		14 gauge
• Zinc Coating		Commercial Class
• Roll Length		100 ft

**DISCLAIMER:** Description regarding the products described herein are based solely upon information provided by the manufacturer and are provided for information purposes only. **NOTHING CONTAINED HEREIN SHOULD BE CONSTRUED AS CREATING AN EXPRESSED OR IMPLIED WARRANTY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS, EACH OF WHICH IS HEREBY DISCLAIMED. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF.** The final determination as to the suitability of any product of L&M Supply in any particular application rests solely with the user. L&M Supply reserves the right to alter or modify its products and descriptions at any time without notice.

**US EROSION  
CONTROL  
PRODUCTS**

[www.siltmanagementsupplies.com](http://www.siltmanagementsupplies.com)