

Silt Management Supplies, LLC.
20439 Westfield Commerce Drive
Katy, Texas 77449-2569
Phone: 281-717-8921
www.siltmanagementsupplies.com

' Z' Dyke Curb Inlet Protection

Product Type: LM600NT 6oz Filter Fabric
Polymer: Polypropylene Staple Fiber
Wire Mesh: 12.5g 2"x4" Openings

Property	Test Procedures	American Standard
• Style		6 Oz
• Grab Tensile	ASTM D 4632	160 Lbs
• Grab Elongation	ASTM D 4632	50%
• CBR Puncture	ASTM D 6241	410 Lbs
• Trapezoid Tear	ASTM D 4533	60 Lbs
• Apparent Opening Size	ASTM D 4751	70 Sieve
• Permittivity	ASTM D 4491	1.5 Sec ⁻¹
• UV Resistance	ASTM D 4355	70% @ 500 hrs
• Water Flow	ASTM D 4491	110 Gpm/Ft

LM 600 NT meets AASHTO M-288-06 Class 2 Standards.

Product Type: 12.5 Gauge 2"x4" Wire

Property	Test Procedures	American Standard
• Wire Space		2"x4"
• Top/Bottom Wires		12.5 gauge
• Vertical/Horizontal Filler Wires		12.5 gauge

Product Lengths:

Z Dyke Curb Inlet Protection come in 8',10' and 12' Lengths.

Disclaimer: L & M Supply assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. L & M Supply disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

Manufactured by: L&M Supply Co. Inc.

**US EROSION
CONTROL
PRODUCTS**

www.siltmanagementsupplies.com