



Triangular Filter Dike

Triangular Filter Dike

Product Type: LM 600 Filter Fabric
Polymer: Polypropylene Staple Fiber

Property	Test Procedures	American Standard
• Style		6 Oz
• Grab Tensile	ASTM D 4632	160 Lbs
• Grab Elongation	ASTM D 4632	50%
• CBR Puncture	ASTM D 6241	410 Lbs
• Trapezoid Tear	ASTM D 4533	60 Lbs
• Apparent Opening Size	ASTM D 4751	70 Sieve
• Permittivity	ASTM D 4491	1.5 Sec ⁻¹
• UV Resistance	ASTM D 4355	70% @ 500 hrs
• Water Flow	ASTM D 4491	110 Gpm/Ft

LM 600 NT meets AASHTO M-288-06 Class 2 Standards.

Product Type: 10 Gauge 6"x6" Wire

Property	Test Procedures	American Standard
• Wire Space		6" x6"
• Top/Bottom Wires		10 gauge
• Vertical/Horizontal Filler Wires		10 gauge

Product Lengths:

Triangular Filter Dikes come in 8' & 10' Lengths.

Disclaimer: L & M Supply assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. L & M Supply disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

www.LandMSupplyTX.com

**US EROSION
CONTROL
PRODUCTS**

L&M Supply Co.

126 Texas Ave. San Marcos TX 78666

Office: (512) 667-6635 Fax: (512) 667-6851