

Fact Sheet June 2015

VOLVOX Dispersion Paint is white wall and ceiling paint for interior use on mineral surfaces such as cement and lime render, brickwork stone and concrete.

VOLVOX Dispersion Paint is suitable for painting organic surfaces such as paper, paper lined plaster board, timber and fabric. It is also suitable for painting glass fibre wall paper.

VOLVOX Dispersion Paint is washable (EN 13 300), fast drying, non-film forming and it retains vapour permeability of the painted surface.

The permanent flexible paint is odourless and free of volatile organic compounds.

VOLVOX Dispersion Paint is so versatile that no primers or undercoats are needed. It has a hiding power of 99.5%.

VOLVOX Dispersion Paint is perfect in creating a warm and cosy feeling in your home. Due to its highly absorbing capabilities, it is also an ideal choice for children's rooms, chemically-sensitive people, asthma sufferers and people with skin problems.

SURFACE PREPARATION

Remove dirt, grease, oil and loose, peeling and flaking material. Fill cracks and holes with a filler. Sand the surface smooth and remove all dust. Light sanding is recommended when painting over firm glossy or semi-gloss paint.

APPLICATION

Apply VOLVOX Dispersion Paint by brush or/and roller and spread evenly in all directions. On very absorbent surfaces such as clay, Gyprock, plaster, sandstone etc. application will be easier by dampening the surface with water. Do not apply in temperatures below 5°C or above 30°C.

DRYING AND RECOATING

VOLVOX Dispersion Paint will normally dry within 2 hours and can then be recoated if necessary. In cold or humid conditions drying time may be lengthened.

COVERAGE

Depending on colour, 1 litre will cover approximately 8 sq. metres with covering capacity of 99.50%

Clean Up

With warm soapy water, away from drains.

COLOURS

VOLVOX Dispersion Paint WHITE can be tinted using our non-toxic pigment pastes to all pastel colours of our Clay Décor range.

STORAGE AND SHELF LIFE

Store tightly sealed, cool but frost free. Minimum shelf life for unopened and properly stored containers is 12 months.

SAFETY

Even though non-toxic, please keep away from children.

DISPOSAL

Allow unwanted paint to dry. Solid matter can be disposed of via the normal garbage collection service.

DISCLAIMER

This technical information is intended to provide guidelines for users. Products are guaranteed to give a satisfactory performance only if used as recommended. Liability shall be limited to refund of purchase price or the replacement of a defective product. There are no other warranties expressed or implied.

It is recommended that the user tests the product on the intended surface to ensure its suitability.

Made in Germany

For further information contact
Amma Earth Products
17/26 Megalong St.
Katoomba NSW 2780
02 47 88 11 17
www.volvoxaustralia.com