

CFA Uni-Form Shell Replaceable Cartridges

F Series, Replaceable Filter Cartridge

- Super-pleated filter media provides up to twice the filter area of any other pleated or non-pleated filter cartridge today
- Traps solid contaminants down to 10 microns in size
- Integral end rings are permanently bonded to filter media
- Stainless steel helical wire spring within the filter eliminates the possibility of cartridge collapse under normal operation conditions



DF Series, Replaceable Dual-Purpose Filter Plus Drier Cartridge

- Molded solid core of specially blended molecular sieve and activated alumina produces a dual-purpose suction line filter/drier of unusually high efficiency and capability
- Can be used for system clean-ups or on a permanent use basis
- Solid contaminants never reach the desiccant core
- Moisture and acids are efficiently removed from the refrigerant stream
- All filters or filters plus driers should be changed when pressure drop across cartridge increases significantly
- All filters or filters plus driers are rated in accordance with ARI standard 730
- Always follow compressor manufacturer's recommendations



Part Number	For Shell Number	Cartridge OD (in.)	Cartridge Length (in.)	Filter Area (in.2)	Standard Package	Weight Per Package (lbs)	UPC Code	Weight (lbs)
F Series								
F25A	2CFA	1 23/32	6 5/16	66	12	4 1/4	8576840755	0.165
F35A	3CFA	2 5/8	6 21/32	115	12	6	8576840756	0.255
F45A	4CFA	3 17/32	7 3/16	189	12	9 3/4	8576840758	0.68
F55A	5CFA	4 1/16	8 3/16	270	12	11 3/4	8576840757	0.67
DF Series								
DF25A	2CFA	1 23/32	6 11/32	66	12	5 3/4	8576840752	0.26
DF35A	3CFA	2 5/8	6 21/32	115	12	10 1/2	8576840794	0.67
DF45A	4CFA	3 17/32	7 7/32	189	12	17 1/4	8576840753	1.255
DF55A	5CFA	4 1/16	8 7/32	270	12	24 1/2	8576840754	1.765