



# 700 FAMILY



Exclusively For Professionals

# 700 FAMILY

Simple. Affordable. Professional.



PRO



**7D** 7 Day Programmable  
**5/1/1** 5/1/1 Programmable  
**NP** Non-Programmable

Model #	7D	5/1/1	NP	Stages Of Heat	Stages Of Cool	Heat Pump Systems With Auxiliary	Conventional Systems	PTAC Mode	Display Size (square inches)	Filter Change Reminder	Room Temperature Calibration	Adjustable Heat & Cool Temperature Swing	Programmable Fan	Adjustable Setpoint Limits	Auto Changeover	Memory Type (non-volatile)	Remote Sensor Capable	Outdoor Temperature Sensor Capable	WIFI Ready	Fan Speeds	Warranty (years)	Terminals
T771			NP	0/1	0/1			4												1	5	R, C, W/Y, G
T755S**	7D	5/1/1	NP	3*	2			7												3	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, S1, S2
T755	7D	5/1/1	NP	3*	2			7												3	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
T731WO			NP	2	1			7												3	5	R, C, Y, W, O, B, GH, GL
T731W			NP	2	1			7												3	5	R, C, Y, W, O, B, GH, GL
T725	7D	5/1/1	NP	2	1			4												1	5	R, C, Y, W2, WE, G, B, O
T721			NP	2	1			4												1	5	R, C, Y, W2, WE, G, B, O
T715	7D	5/1/1	NP	2	2			4												1	5	Rh, Rc, C, Y, Y2, W, W2, G, B, O
T705	7D	5/1/1	NP	1	1			4												1	5	Rh, Rc, C, Y, W, G, B, O
T701i			NP <sup>4</sup>	1	1			4												1	5	Rh, Rc, C, Y, W, G, B, O
T701			NP	1	1			4												1	5	Rh, Rc, C, Y, W, G, B, O

<sup>4</sup> Programming available through the WIFI app  
 Stages\* = 2 Stages For Conventional Heat

\*\* Wired accessories available for T755S  
**R251S** is an indoor remote temperature sensor  
**R250S** is an outdoor remote temperature sensor



The most commonly desired features at a great value with a model for nearly any system.

rev. 2018



1-800-PRO1-559 (776-1559)

PRO  
 www.proTiaq.com