



# PRO1 SUBMITTAL SHEET

Job Name: \_\_\_\_\_ Location: \_\_\_\_\_ Date: \_\_\_\_\_

Purchaser: \_\_\_\_\_ Installer: \_\_\_\_\_

Submitted to: \_\_\_\_\_ For:  RNC  R&R  Commercial

## MODEL T955S

Universal

Residential / Light commercial

Up to 2 Heat, 2 Cool Conventional

Up to 3 Heat, 2 Cool Heat Pump

Battery or Hardwire

7 Day, 5/1/1 or Non-Programmable



### This model features:

- 13 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Keypad lockout
- Adjustable setpoint limits
- Simple private label badge system
- Auto changeover
- Set dual fuel balance points (R250S)
- Compatible with indoor remote sensors (R251S)
- 5 Year Warranty
- Separate heating and cooling swing (cycle rate) adjustments
- 5 minute compressor delay protection (selectable on or off)
- Universal subbase
- Battery or 24v power
- Programmable Fan
- Remote Sensing

### Specifications:

Application	Up to 2 Heat, 2 Cool Conventional / Up to 3 Heat, 2 Cool Heat Pump
Programmability	7 Day, 5/1/1 or Non-Programmable
Changeover	System Switch
Display Range	41°F to 95°F (5°C to 35°C)
Control Range	44°F to 90°F (7°C to 32°C)
Display Accuracy	+/- 1°F
Heat Swing	Adjustable from 0.2°F to 2.0°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Terminals	Rc, Rh, C, Y, Y2, W/E, W2, G, O, B, S1, S2
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating Ambient	32°F to +105°F (0°C to +41°C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions	4.7"W x 4.4"H x 1.1"D (119mm W x 112mm H x 28mm D)
Warranty	5 year warranty