

Job Name:	
Tag#	



## Submittal Data Sheet

FTX30NVJU / RK30NMVJUA

2.5-Ton Wall Mounted Cooling Only System



### Efficiency

Cooling	
SEER	17.50
EER	9.85

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	31,400 (10,200 / 31,400)
Sensible @ AHRI	21,030
Standard Operating Range	50°F – 115 °F
Extended Operating Range*	-22°F – 115 °F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

\*With field settings and wind baffle

Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). Warranty registration not required to receive the 10-Year parts limited warranty for residential or commercial installations.

### Indoor Specifications

Airflow Rate (cfm)	Cooling	
	H	M
	890	727
	L	SL
	572	512
Sound (dBA) H / M / L / SL	53 / 47 / 40 / 37	
Dimensions (H × W × D) (in)	13-3/8 × 47-1/4 × 10-3/16	
Weight (Lbs)	38	

### Electrical

	208/60/1	230/60/1
System MCA	17	17
System MFA	20	20
Compressor RLA	16.25	16.25
Outdoor fan motor FLA	.62	.62
Outdoor fan motor W	93	93
Indoor fan motor FLA	.37	.37
Indoor fan motor W	64	64

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)  
RLA: Rated load amps (A) W: Fan motor rated output (W)

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type	
Refrigerant	R-410A	
Factory Charge (Lbs)	3.64	
Refrigerant Oil	PVE (FVC50K)	
Airflow Rate (cfm)	Cooling	
	H	2,528
Sound Pressure Level (dBA)	56	
Dimensions (H × W × D) (in)	28-15/16 × 34-1/4 × 12-5/8	
Weight (Lbs)	133	


### Piping

Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.625
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.32

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)






Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



# RK30NMVJUA Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



Indoor Unit		
Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter
	BRC944B2-A08	Wired Remote Controller kit
	BRCW901A08	Wired Remote Controller Cable – 25ft (included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10 ft
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET

Outdoor Unit		
Included	Part Number	Description
	KPW063B4	Air Adjustment Grille (RX & RK)
	KKG063A42	Back protection wire net



Job Name:	
Tag#	



## Submittal Data Sheet

FTX36NVJU / RK36NMVJUA

3-Ton Wall Mounted Cooling Only System



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). Warranty registration not required to receive the 10-Year parts limited warranty for residential or commercial installations.

### Indoor Specifications

Airflow Rate (cfm)	Cooling	
	H	M
	915	742
	L	SL
	572	512
Sound (dBA) H / M / L / SL	54 / 47 / 40 / 37	
Dimensions (H x W x D) (in)	13-3/8 x 47-1/4 x 10-3/16	
Weight (Lbs)	38	

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type	
Refrigerant	R-410A	
Factory Charge (Lbs)	3.64	
Refrigerant Oil	PVE (FVC50K)	
Airflow Rate (cfm)	Cooling	
	H	2,811
Sound Pressure Level (dBA)	59	
Dimensions (H x W x D) (in)	28-15/16 x 34-1/4 x 12-5/8	
Weight (Lbs)	133	

### Efficiency

Cooling	
SEER	15.90
EER	9.10

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	34,400 (10,200 / 34,400)
Sensible @ AHRI	22,160
Standard Operating Range	50°F – 115°F
Extended Operating Range*	-22°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

\*With field settings and wind baffle

### Electrical

	208/60/1	230/60/1
System MCA	17	17
System MFA	20	20
Compressor RLA	16.25	16.25
Outdoor fan motor FLA	.83	.83
Outdoor fan motor W	123	123
Indoor fan motor FLA	.37	.37
Indoor fan motor W	64	64

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)

RLA: Rated load amps (A) W: Fan motor rated output (W)

### Piping

Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.625
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.32


Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: May 2020

Page 1 of 4






Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



# RK36NMVJUA Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



Indoor Unit		
Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter
	BRC944B2-A08	Wired Remote Controller kit
	BRCW901A08	Wired Remote Controller Cable – 25 ft (included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10 ft
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET

Outdoor Unit		
Included	Part Number	Description
	KPW063B4	Air Adjustment Grille (RX & RK)
	KKG063A42	Back protection wire net



Job Name:	
Tag#	



## Submittal Data Sheet

FTX30NVJU / RX30NMVJUA

2.5-Ton Wall Mounted Heat Pump System



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). Warranty registration not required to receive the 10-Year parts limited warranty for residential or commercial installations.

### Indoor Specifications

Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	890	727	960	791
Sound (dBA) H / M / L / SL	L	SL	L	SL
	572	512	629	544
Sound (dBA) H / M / L / SL		53 / 47 / 40 / 37		53 / 46 / 38 / 35
Dimensions (H x W x D) (in)		13-3/8 x 47-1/4 x 10-3/16		
Weight (Lbs)		38		

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Factory Charge (Lbs)	3.64			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
		2,528		2,274
Sound Pressure Level (dBA)	56 / 58			
Dimensions (H x W x D) (in)	28-15/16 x 34-1/4 x 12-5/8			
Weight (Lbs)	133			

### Efficiency

Cooling		Heating	
SEER	17.5	HSPF	9.3
EER	9.85	COP	2.92

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	31,400 (10,200 / 31,400)
Sensible @ AHRI	21,030
Standard Operating Range	50°F – 115°F
Extended Operating Range*	-4°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

\*With field settings and wind baffle

Heating (Btu/hr)	
1: @ 47° Rated (Min/Max)	34,800 (10,200 / 34,800)
2: @ 17° Rated	22,400
3: @ 5°	15,550
Operating Range	5 – 65°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 47°F DB/43°F WB  
2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 17°F DB/15°F WB  
3: Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 5°F DB/5°F WB

### Electrical

	208/60/1	230/60/1
System MCA	19.8	19.8
System MFA	20	20
Compressor RLA	18.25	18.25
Outdoor fan motor FLA	.62	.62
Outdoor fan motor W	93	93
Indoor fan motor FLA	.37	.37
Indoor fan motor W	64	64

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)  
RLA: Rated load amps (A) W: Fan motor rated output (W)

### Piping

Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.625
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.32


Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: May 2020

Page 1 of 4






Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



# RX30NMVJUA Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



Indoor Unit		
Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter
	BRC944B2-A08	Wired Remote Controller kit
	BRCW901A08	Wired Remote Controller Cable – 25 ft (included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10 ft
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET

Outdoor Unit		
Included	Part Number	Description
	KEH063A4E	Drain Pan Heater (RX)
	KPW063B4	Air Adjustment Grille (RX & RK)
	KKG063A42	Back protection wire net



Job Name:	
Tag#	



## Submittal Data Sheet

FTX36NVJU / RX36NMVJUA

3-Ton Wall Mounted Heat Pump System



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). Warranty registration not required to receive the 10-Year parts limited warranty for residential or commercial installations.

### Indoor Specifications

Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	915	742	960	791
	L	SL	L	SL
	572	512	629	544
Sound (dBA) H / M / L / SL	54 / 47 / 40 / 37		53 / 46 / 38 / 35	
Dimensions (H × W × D) (in)		13-3/8 × 47-1/4 × 10-3/16		
Weight (Lbs)		38		

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Factory Charge (Lbs)	3.64			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	2,811	H	2,352
Sound Pressure Level (dBA)	59			
Dimensions (H x W x D) (in)	28-15/16 x 34-1/4 x 12-5/8			
Weight (Lbs)	133			

### Efficiency

Cooling		Heating	
SEER	15.9	HSPF	9.2
EER	9.10	COP	2.78

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	34,400 (10,200 / 34,400)
Sensible @ AHRI	22,160
Standard Operating Range	50°F – 115°F
Extended Operating Range*	-4°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

\*With field settings and wind baffle

Heating (Btu/hr)	
1: @ 47° Rated (Min/Max)	36,000 (10,200 / 36,000)
2: @ 17° Rated	22,800
3: @ 5°	15,740
Operating Range	5 – 65°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 47°F DB/43°F WB  
2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 17°F DB/15°F WB  
3: Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 5°F DB/5°F WB

### Electrical

	208/60/1	230/60/1
System MCA	19.8	19.8
System MFA	20	20
Compressor RLA	18.25	18.25
Outdoor fan motor FLA	.83	.83
Outdoor fan motor W	123	123
Indoor fan motor FLA	.37	.37
Indoor fan motor W	64	64

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)  
RLA: Rated load amps (A) W: Fan motor rated output (W)

### Piping

Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.625
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.32

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056


(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: May 2020

Page 1 of 4



# FTX36NVJU Dimensional Data




Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



# RX36NMVJUA Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: May 2020

Page 3 of 4



Indoor Unit		
Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter
	BRC944B2-A08	Wired Remote Controller kit
	BRCW901A08	Wired Remote Controller Cable – 25 ft (included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10ft
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET

Outdoor Unit		
Included	Part Number	Description
	KEH063A4E	Drain Pan Heater (RX)
	KPW063B4	Air Adjustment Grille (RX & RK)
	KKG063A42	Back protection wire net