



KNOCKDOWN

DESCRIPTION:

F9 Knockdown is an extremely low-foaming cleaner/degreaser/neutralizer designed for use on parking garages, airports, drive thru's and gas stations. It can be used with ride-on equipment such as Cyclone machinery and Sirocco water recovery equipment without the foaming problems found with traditional alkaline cleaners. F9 Knockdown is an environmentally friendly product, easily biodegradable and has no VOC's, phosphates or chlorinated solvents. Additionally, it has zero fuming or vapors.

LIMITATIONS:

May cause damage to some metallic surfaces or diamond plate.

Always test first before full scale cleaning

SAFETY INFORMATION:

Always perform a test in an inconspicuous area before cleaning. A simple test will tell you what dilution, ration and process to use and let you see if there are any unwanted reactions with surface. Read the SDS before application. Read "Warning of Danger" and any other warnings on label before application.

ADVANTAGES:

- Low foam, no color
- Neutralizes battery (sulfuric acid) stains from Electric Vehicles
- Cuts and helps to remove oils, soils, food and petroleum stains.
- Removes diesel spills.
- Great for carbon stains
- Water based and enviro-friendly.
- Non-Flammable
- Phosphate Free
- No VOC's, Chlorinated Solvents, Fumes or Vapors

SURFACE AND AIR TEMPERATURES:

Extremely high temperatures (>115F) and extremely low temperatures (<50F) may slow the product down from working as efficiently as possible. More product or a longer dwell time may be needed. If surface to be cleaned is frozen, allow time to thaw before application.

SUITABLE SURFACES:

Concrete, brick, pavers, tile, stone, grout, masonry, stucco, older asphalt, vinyl, painted surfaces (test first)



KNOCKDOWN

DILUTIONS:

Water to Product
Very Heavily Soiled: Straight to 1:1
Heavily Soiled: 1:1 to 4:1
Moderately soiled 4:1-10:1
Lightly Soiled 10:1-20:1
Neutralizing Acid Stains: 4:1 to 10:1

INSTRUCTIONS FOR APPLICATION:

Apply on a dry surface, using a dedicated pump sprayer, electric or air diaphragm sprayer. Dwell 10-30 minutes and power wash or surface clean. Hand brushing may be useful (stiff nylon deck brush) or use the 175 Floor Tool with brush.

STORAGE:

Always store in a cool, dry place away from low pH products. Do not allow product to freeze.

WARRANTY:

ALWAYS PERFORM A TEST SAMPLE TO DETERMINE DESIRED RESULTS. PRODUCT FREEZES BELOW 32°F, AND MAY BE ADVERSELY AFFECTED BY COLD WEATHER.

WARRANTY CONTINUED:

FRONT 9 RESTORATION INC., warrants that the product will conform to the description and specifications set forth on the product label and will be free from defects in material and workmanship. The exclusive remedy of the Buyer in the event that the product does not so conform shall be the replacement of the product. This warranty is expressly made in lieu of any, and all other warranties expressed or implied including the warranties of merchantability and fitness, and FRONT 9 RESTORATION, INC., shall not be liable for any loss or damage, directly or indirectly arising from the use of such merchandise or for consequential or incidental damages. While FRONT 9 RESTORATION INC., believes that the data contained herein is accurate and the information is based on test and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Manufacturer shall not be responsible for any contamination, or related testing or removal costs resulting from use of this lead-free product on any material containing lead or toxic or environmentally hazardous substances. Since the actual use, by others is beyond our control, no guarantee, expressed or implied is made by FRONT 9 RESTORATION INC., as to the effects of such use, the results to be obtained, or the safety toxicity of the product referred to herein. Nor is the information herein to be construed as complete since additional information may be necessary or desirable when particular conditions or circumstances exist or because of applicable laws or governmental regulations. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration rules of the American Arbitration Association.