

Version 1.13 Revision Date: 09/15/2023

SECTION 1. IDENTIFICATION

Product name : ISOPROPANOL 99%

Synonyms : 2-PROPANOL; ISOPROPYL ALCOHOL; IPA ; propan-2-ol

Recommended use of the chemical and restrictions on use

Recommended use : Alcohol solvent

Restricted Uses : No data available

Manufacturer or supplier's details

Company : Univar Solutions Canada Ltd.

Address 64 Arrow Road

North York, ON, M9M 2L9

Canada

Emergency telephone number:

Local Emergency Contact: During Office hours Monday-Friday, 8.00 am - 4.30 pm (Pacific

Standard Time): 1-866-686-4827

Additional Information: : Responsible Party: Product Compliance Department

E-mail: SDSNA@univarsolutions.com SDS Requests: 1-855-429-2661 Website: www.univarsolutions.com

SECTION 2. HAZARD IDENTIFICATION

Hazardous Classification of the substance or mixture

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

Label elements

Hazard pictograms

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equip-

SDS Number: 100000002859 1 / 9 ISOPROPANOL 99%



Version 1.13 Revision Date: 09/15/2023

ment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	% by Weight	Synonyms
67-63-0	Isopropyl alcohol	80 - 100	propan-2-ol

The exact ranges of this mixture are being withheld due to a Trade Secret.

SECTION 4. FIRST-AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

SDS Number: 100000002859 2 / 9 ISOPROPANOL 99%



Version 1.13 Revision Date: 09/15/2023

In case of eye contact : Immediately flush eye(s) with plenty of water.

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Do not induce vomiting without medical advice.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Specific hazards during firefighting

Hazardous combustion prod-

: High volume water jet

: Do not allow run-off from fire fighting to enter drains or water courses.

ucts

Carbon oxides

formaldehyde corrosive vapors Nitrogen oxides (NOx)

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

: Prevent product from entering drains. **Environmental precautions**

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

SDS Number: 100000002859 3/9 **ISOPROPANOL 99%**



Version 1.13 Revision Date: 09/15/2023

miculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

: Avoid formation of aerosol. Advice on safe handling

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation

hood.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
67-63-0	Isopropyl alcohol	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
_		STEV	400 ppm	CA QC OEL

Personal protective equipment

Use respiratory protection unless adequate local exhaust Respiratory protection

ventilation is provided or exposure assessment demonstrates

SDS Number: 100000002859 **ISOPROPANOL 99%** 4/9



Version 1.13 Revision Date: 09/15/2023

that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection

Material : Nitrile (Not the single use kind) or Neoprene Gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Clear, colorless

Odour : alcohol-like, characteristic

Odour Threshold : 200 ppm

pH : neutral

Freezing Point (Melting

point/freezing point)

: -88 °C (-126 °F)

Boiling Point (Boiling

: 82 - 83 °C (180 - 181 °F)

point/boiling range) (1013 hPa)

Flash point : 12 °C (54 °F)

Method: Tag closed cup

Evaporation rate : < 3.9

(Butyl Acetate = 1)

Flammability (solid, gas)

: No data available

Upper explosion limit : 13 %(V)

Lower explosion limit : 2 %(V)

Vapour pressure : No data available

Relative vapour density : < 2.1 @ 15 - 20 °C (59 - 68 °F)

(Air = 1.0)

Relative density : 0.785 - 0.787 @ 20 °C (68 °F)

Reference substance: (water = 1)

Density : 0.785 - 0.787 g/cm3 @ 20 °C (68 °F)

Solubility(ies)

SDS Number: 100000002859 5 / 9 ISOPROPANOL 99%



Version 1.13 Revision Date: 09/15/2023

Water solubility : completely miscible

Solubility in other solvents : No data available Partition coefficient: n- : log Pow: 0.05 @ 2 : log Pow: 0.05 @ 25 °C (77 °F)

octanol/water

: 399 - 425 °C Auto-ignition temperature : No data available Thermal decomposition

Viscosity

Viscosity, dynamic : 2.4 mPa.s @ 20 °C (68 °F)

Viscosity, kinematic : 2.66 mm2/s @ 25 °C (77 °F)

Surface tension : 22.7 mN/m, 20 °C

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Vapours may form explosive mixture with air.

: Keep away from heat, flame, sparks and other ignition Conditions to avoid

sources.

Incompatible materials : Strong acids

Aldehydes

Oxidizing agents

Rubber Oils **Plastics Amines**

Halogenated compounds

Peroxides Bases

Hazardous decomposition

products

: Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Serious eye damage/eye irritation

Components:

67-63-0:

Species: Rabbit

Result: Irritating to eyes.

STOT - single exposure

Components:

67-63-0:

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

SDS Number: 100000002859 **ISOPROPANOL 99%** 6/9



Version 1.13 Revision Date: 09/15/2023

posure, category 3 with narcotic effects.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Uni-

var Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

TDG (Transportation of Dangerous Goods):

UN1219, ISOPROPANOL, 3, II

SDS Number: 100000002859 7 / 9 ISOPROPANOL 99%



Version 1.13 Revision Date: 09/15/2023

IATA (International Air Transport Association):

UN1219, ISOPROPANOL, 3, II

IMDG (International Maritime Dangerous Goods):

UN1219, ISOPROPANOL, 3, II, Flash Point:12 °C(54 °F)

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

NPRI Components : 67-63-0

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PHIL : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions EHS Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 09/15/2023

Legacy SDS: : R0001444, 100000027693, 100000061297

Material number:

16209525, 16207322, 16207529, 16207396, 16205633, 16185017, 16204322, 16203651, 16141730, 16187819, 16141123, 16185016, 16187197, 16185038, 16185039, 16184473, 16184512, 16184020, 16184810, 16184408, 16184314, 16185097, 16186271, 16183109, 16182974, 16178967, 16182648, 16175816, 16176549, 16175656, 16176457, 16176751,

SDS Number: 100000002859 8 / 9 ISOPROPANOL 99%



Version 1.13 Revision Date: 09/15/2023

16175879, 16174714, 16176870, 16175445, 16174727, 16174726, 16175555, 16180539, 16163494, 16151614, 16169230, 16169779, 16168235, 16170647, 16170200, 16170163, 16168234, 16173689, 16172502, 16145669, 16149765, 16171308, 16158552, 16146859, 16147074, 16147313, 16148783, 16148704, 16144452, 16146351, 16146089, 16144123, 16143652, 16167327, 16166321, 16165964, 16161591, 16149329, 16158191, 16152613, 16138602, 16137598, 16143917, 16140147, 16138087, 16137628, 16137534, 16137389, 16137356, 16156747, 16145782, 16160060, 16154121, 16159435, 16144176, 16152980, 16144004, 16153058, 16135462, 16143649, 16143998, 16148561, 16148563, 16135027, 16141526, 16159251, 16159182, 16143653

Key or leg	end to abbreviations and acronyms	used in the	safety data sheet
ACGIH	American Conference of Gov-	LD50	Lethal Dose 50%
	ernment Industrial Hygienists		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Sub- stances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50		Lethal Cond	centration 50%