

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier PHB

Other means of identificationNot availableRecommended useModelling ClayRecommended restrictionsNone known.

Manufacturer information Tucker's Pottery Supplies Inc.,

Cone Art Kilns Inc. 15 West Pearce Street

Richmond Hill, ON L4B 1H6 CA Phone: Toll Free 1-800-304-6185

Phone: 905-889-7705

Emergency Phone Number: 613-996-6666 (CANUTEC)

Supplier See above.

2. Hazards Identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

WHMIS 2015 defined hazards Not classified

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or

smoke when using this product.

Response IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS 2015: Health Hazard(s)

not otherwise classified

(HHNOC)

WHMIS 2015: Physical

Hazard(s) not otherwise classified (PHNOC)

Hazard(s) not otherwise classified (HNOC)

None known

None known

None known.

Supplemental information None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Crystalline silica		14808-60-7	37
Kaolin		1332-58-7	29
Dolomite		16389-88-1	10

#28953 Page: 1 of 11 Issue date 14-February-2018

Chemical name	Common name and synonyms	CAS number	%
Titanium oxide		13463-67-7	1
Tremolite (Non-asbestiform)		14567-73-8	0.1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. F	First	Aid	Measures
------	-------	-----	----------

Inhalation
Skin contact
Eye contact

If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.

Ingestion

Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.

Most important

symptoms/effects, acute and delayed

Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

Hazardous combustion

May include and are not limited to: Silicon tetrafluoride. Hydrofluoric acid.

products

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. When using, do not eat, drink or smoke. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

#28953 Page: 2 of 11 Issue date 14-February-2018

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupation Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Dolomite (CAS 16389-88-1)	TWA	3 mg/m3 10 mg/m3	Respirable particles. Total particulate.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.
Titanium oxide (CAS 13463- 67-7)	TWA	10 mg/m3	·
Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	0.1 fibers/cm3	
Canada. British Columbia OELs. (C Safety Regulation 296/97, as amen		s for Chemical Substances, Occ	cupational Health and
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Dolomite (CAS 16389-88-1)	TWA	3 mg/m3	Respirable fraction.
W15- (OAO 4000 50 7)	TIALA	10 mg/m3	Total dust.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.
Titanium oxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	0.1 fibers/cm3	
Canada. Manitoba OELs (Reg. 217/ Components	2006, The Workplace Safety Type	And Health Act) Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Titanium oxide (CAS 13463- 67-7)	TWA	10 mg/m3	
Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	0.1 fibers/cm3	Fiber.
Canada. Ontario OELs. (Control of Components	Exposure to Biological or Ch Type	nemical Agents) Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Dolomite (CAS 16389-88-1)	TWA	3 mg/m3 10 mg/m3	Respirable fraction. Inhalable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Titanium oxide (CAS 13463- 67-7)	TWA	10 mg/m3	
Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	0.1 fibers/ml	Respirable fibers.
Canada. Quebec OELs. (Ministry of Components	Labor - Regulation Respect Type	ing the Quality of the Work Env Value	ironment) Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Dolomite (CAS 16389-88-1)	TWA	10 mg/m3	Total dust.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.
Titanium oxide (CAS 13463- 67-7)	TWA	10 mg/m3	Total dust.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	STEL	5 fibers/cm3n	Respirable fibers.
	TWA	1 fibers/cm3n	Respirable fibers.

#28953 Page: 3 of 11 Issue date 14-February-2018

Components	lated Substances (29 CFR 1910.1001-1050) Type	Value	
Tremolite (Non-asbestiform) (CAS 14567-73-8)	STEL	1 fibers/cm3	
(TWA	0.1 fibers/cm3	
	for Air Contaminants (29 CFR 1910.1000)		_
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Titanium oxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF		., .	.
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
,		2.4 mppcf	Respirable.
Dolomite (CAS 16389-88-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
K1- (040 4000 	T1444	15 mppcf	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust. Total dust.
		50 mppcf 15 mppcf	Respirable fraction.
Titanium oxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
10700-01-1)		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values	•	•
Components	Type	Value	Form
·	TWA	0.025 mg/m3	Respirable fraction.
14808-60-7)	TWA	2 mg/m3	Respirable fraction.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-	TWA TWA	2 mg/m3 10 mg/m3	Respirable fraction.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform)		· ·	Respirable fraction. Fiber.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	10 mg/m3	·
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to	TWA	10 mg/m3	·
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS	TWA TWA Chemical Hazards	10 mg/m3 0.1 fibers/cm3	Fiber.
Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7)	TWA TWA Chemical Hazards Type	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 5 mg/m3	Fiber. Form
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7)	TWA TWA Chemical Hazards Type TWA TWA	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 5 mg/m3 10 mg/m3	Fiber. Form Respirable dust. Respirable.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values	TWA TWA Chemical Hazards Type TWA TWA TWA No biological exposure limits noted for the ingreen	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 5 mg/m3 10 mg/m3 edient(s).	Fiber. Form Respirable dust. Respirable. Total
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values	TWA TWA Chemical Hazards Type TWA TWA	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 5 mg/m3 10 mg/m3 edient(s).	Fiber. Form Respirable dust. Respirable. Total
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values osure guidelines ropriate engineering	TWA TWA Chemical Hazards Type TWA TWA No biological exposure limits noted for the ingree Occupational exposure to nuisance dust (total at	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 10 mg/m3 edient(s). and respirable) and resper hour) should be use process enclosure ne levels below recom	Fiber. Form Respirable dust. Respirable. Total spirable crystalline silica e used. Ventilation rates es, local exhaust ventilation mended exposure limits.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values osure guidelines ropriate engineering trols	TWA TWA Chemical Hazards Type TWA TWA No biological exposure limits noted for the ingree Occupational exposure to nuisance dust (total a should be monitored and controlled. Good general ventilation (typically 10 air chang should be matched to conditions. If applicable, or other engineering controls to maintain airborn	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 10 mg/m3 edient(s). and respirable) and resper hour) should be use process enclosure ne levels below recom	Fiber. Form Respirable dust. Respirable. Total spirable crystalline silica e used. Ventilation rates es, local exhaust ventilation mended exposure limits.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values osure guidelines ropriate engineering trols	TWA TWA Chemical Hazards Type TWA TWA TWA No biological exposure limits noted for the ingree Occupational exposure to nuisance dust (total a should be monitored and controlled. Good general ventilation (typically 10 air chang should be matched to conditions. If applicable, or other engineering controls to maintain airborn exposure limits have not been established, mai	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 10 mg/m3 edient(s). and respirable) and resper hour) should be use process enclosure ne levels below recom	Fiber. Form Respirable dust. Respirable. Total spirable crystalline silica e used. Ventilation rates es, local exhaust ventilation mended exposure limits.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values osure guidelines propriate engineering trols	TWA TWA Chemical Hazards Type TWA TWA TWA No biological exposure limits noted for the ingree Occupational exposure to nuisance dust (total a should be monitored and controlled. Good general ventilation (typically 10 air chang should be matched to conditions. If applicable, or other engineering controls to maintain airborn exposure limits have not been established, mai such as personal protective equipment	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 10 mg/m3 edient(s). and respirable) and resper hour) should be use process enclosure ne levels below recom	Fiber. Form Respirable dust. Respirable. Total spirable crystalline silica e used. Ventilation rates es, local exhaust ventilation mended exposure limits.
14808-60-7) Kaolin (CAS 1332-58-7) Titanium oxide (CAS 13463-67-7) Tremolite (Non-asbestiform) (CAS 14567-73-8) US. NIOSH: Pocket Guide to Components Crystalline silica (CAS 14808-60-7) Kaolin (CAS 1332-58-7) ogical limit values osure guidelines cropriate engineering trols vidual protection measures, Eye/face protection	TWA TWA Chemical Hazards Type TWA TWA TWA No biological exposure limits noted for the ingree Occupational exposure to nuisance dust (total a should be monitored and controlled. Good general ventilation (typically 10 air chang should be matched to conditions. If applicable, or other engineering controls to maintain airborn exposure limits have not been established, mai such as personal protective equipment	10 mg/m3 0.1 fibers/cm3 Value 0.05 mg/m3 10 mg/m3 edient(s). and respirable) and resper hour) should be use process enclosure ne levels below recomntain airborne levels to	Fiber. Form Respirable dust. Respirable. Total spirable crystalline silica e used. Ventilation rates es, local exhaust ventilation mended exposure limits.

#28953 Page: 4 of 11 Issue date 14-February-2018

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respiratory protection

> Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134),

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance Moist mud Physical state Solid. Solid. **Form** Color grey Odor Earthy

Odor threshold Not available. Not available. pН Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Not available. Pour point Specific gravity Not available. Partition coefficient Not available. (n-octanol/water)

Flash point Not available. **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not applicable.

Flammability limit - upper

(%)

Not available. Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available. Not available. Relative density Solubility(ies) Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

10. Stability and Reactivity

Reactivity This product may react with strong oxidizing agents.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Chemical stability Material is stable under normal conditions.

Conditions to avoid Do not mix with other chemicals. Incompatible materials Powerful oxidizers. Chlorine.

Hazardous decomposition

products

May include and are not limited to: Hydrofluoric acid. Silicon tetrafluoride.

11. Toxicological Information

Inhalation. Eye, Skin contact, Inhalation, Ingestion. Routes of exposure

#28953 Page: 5 of 11 Issue date 14-February-2018 Information on likely routes of exposure

Ingestion May cause stomach distress, nausea or vomiting.

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may result in mechanical irritation.

Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Components Species Test Results

Crystalline silica (CAS 14808-60-7)

Acute

Dermal

LD50 Not available

Inhalation

LC50 Not available

Oral

LD50 Rat 500 mg/kg, HSDB, IV only

Dolomite (CAS 16389-88-1)

Acute

Dermal

LD50 Not available

Inhalation

LC50 Not available

Oral

LD50 Not available

Kaolin (CAS 1332-58-7)

Acute

Dermal

LD50 Rat > 5000 mg/kg, HSDB

Inhalation

LC50 Not available

Oral LD50

Rat > 5000 mg/kg, HSDB

14900 mg/kg, Gelest

Titanium oxide (CAS 13463-67-7)

Acute

Dermal

LD50 Not available

Inhalation

LC50 Rat > 6.8 mg/L, 4 Hours, ECHA

> 3.6 mg/l/4h, ECHA

> 3.6 mg/L, 4 Hours, ECHA > 2.3 mg/L, 4 Hours, ECHA 5.1 mg/L, 4 Hours, ECHA 3.4 mg/L, 4 Hours, ECHA

Oral

LD50 Mouse > 5000 mg/kg, ECHA

Rat > 25000 mg/kg, ECHA

> 11000 mg/kg, ECHA> 5000 mg/kg, ECHA> 2000 mg/kg, ECHA

#28953 Page: 6 of 11 Issue date 14-February-2018

Components Species Test Results

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Acute Dermal

LD50 Not available

Inhalation

LC50 Not available

Oral

LD50 Not available

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Exposure minutesNot available.Erythema valueNot available.Oedema valueNot available.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Corneal opacity valueNot available.Iris lesion valueNot available.Conjunctival reddeningNot available.

value

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Titanium oxide (CAS 13463-67-7)

Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits.

Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

High concentrations of pigment-grade (powdered) and ultrafine titanium dioxide (titanium oxide) dust have caused respiratory tract cancer in rats exposed by inhalation and intratracheal

instillation

ACGIH Carcinogens

Crystalline silica (CAS 14808-60-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

A2 Suspected human carcinogen.

A1 Confirmed human carcinogen.

Canada - Alberta OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Suspected human carcinogen.

Confirmed human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ASBESTOS, ALL FORMS (CAS 14567-73-8)

SILICA, CRYSTALLINE-.ALPHA.-QUARTZ,
RESPIRABLE FRACTION (CAS 14808-60-7)

Confirmed human carcinogen.

Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7)

Suspected carcinogenic effect in humans.

#28953 Page: 7 of 11 Issue date 14-February-2018

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Detected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (CAS 14808-60-7) Titanium oxide (CAS 13463-67-7)

Volume 68, Volume 100C 1 Carcinogenic to humans. Volume 47, Volume 93 - 2B Possibly carcinogenic to humans.

Tremolite (Non-asbestiform) (CAS 14567-73-8) Volume 14, Supplement 7, Volume 100C 1 Carcinogenic to

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7) Titanium oxide (CAS 13463-67-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US NTP Report on Carcinogens: Known carcinogen

Crystalline silica (CAS 14808-60-7) Known To Be Human Carcinogen. Tremolite (Non-asbestiform) (CAS 14567-73-8) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7) Cancer Tremolite (Non-asbestiform) (CAS 14567-73-8) Cancer

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Teratogenicity Not available. Specific target organ toxicity single exposure

Not classified.

Specific target organ toxicity -

Causes damage to organs through prolonged or repeated exposure.

repeated exposure

Aspiration hazard Not an aspiration hazard.

Causes damage to organs through prolonged or repeated exposure. **Chronic effects**

Prolonged exposure may cause chronic effects.

Prolonged or repeated exposure to fine airborne crystalline silica dust may cause severe scarring of the lungs, a disease called silicosis. Early symptoms of silicosis include cough, mucous

production and shortness of breath upon exertion.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components **Species Test Results**

Titanium oxide (CAS 13463-67-7)

Aquatic

EC50 Water flea (Daphnia magna) > 1000 mg/L, 48 hours Crustacea Fish LC50 Mummichog (Fundulus heteroclitus) > 1000 mg/L, 96 hours

Persistence and degradability No data is available on the degradability of this product.

No data available. Bioaccumulative potential Mobility in soil No data available. Mobility in general Not available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification

In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

#28953 Page: 8 of 11 Issue date 14-February-2018

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

 Dolomite (CAS 16389-88-1)
 Listed.

 Kaolin (CAS 1332-58-7)
 Listed.

 Titanium oxide (CAS 13463-67-7)
 Listed.

 Tremolite (Non-asbestiform) (CAS 14567-73-8)
 Listed.

Canada DSL Challenge Substances: Listed substance

Crystalline silica (CAS 14808-60-7)

Canada Priority Substances List (Second List): Listed substance

Dolomite (CAS 16389-88-1)

Kaolin (CAS 1332-58-7)

Titanium oxide (CAS 13463-67-7)

Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Tremolite (Non-asbestiform) (CAS 14567-73-8) 0.1 % Annual Export Notification required.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium carbonate (CAS 513-77-9) Listed.
Tremolite (Non-asbestiform) (CAS 14567-73-8) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7)

Cancer

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Cancer
Crystalline silica (CAS 14808-60-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Lung

Crystalline silica (CAS 14808-60-7) immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

No

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.Tremolite (Non-asbestiform)14567-73-80.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Barium carbonate (CAS 513-77-9) Listed. Tremolite (Non-asbestiform) (CAS 14567-73-8) Listed.

#28953 Page: 9 of 11 Issue date 14-February-2018

US - Illinois Chemical Safety Act: Listed substance

Barium carbonate (CAS 513-77-9)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US - Louisiana Spill Reporting: Listed substance

Tremolite (Non-asbestiform) (CAS 14567-73-8) Listed.

US - Minnesota Haz Subs: Listed substance

Barium carbonate (CAS 513-77-9)
Listed.
Crystalline silica (CAS 14808-60-7)
Listed.
Dolomite (CAS 16389-88-1)
Listed.
Kaolin (CAS 1332-58-7)
Listed.
Titanium oxide (CAS 13463-67-7)
Listed.
Tremolite (Non-asbestiform) (CAS 14567-73-8)
Listed.

US - New Jersey RTK - Substances: Listed substance

Barium carbonate (CAS 513-77-9) Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Titanium oxide (CAS 13463-67-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US - North Carolina Toxic Air Pollutants: Listed substance

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US - Texas Effects Screening Levels: Listed substance

Barium carbonate (CAS 513-77-9)

Crystalline silica (CAS 14808-60-7)

Dolomite (CAS 16389-88-1)

Kaolin (CAS 1332-58-7)

Titanium oxide (CAS 13463-67-7)

Listed.

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Listed.

Listed.

US. Massachusetts RTK - Substance List

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Titanium oxide (CAS 13463-67-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US. New Jersey Worker and Community Right-to-Know Act

Barium carbonate (CAS 513-77-9)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Barium carbonate (CAS 513-77-9)

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Titanium oxide (CAS 13463-67-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US. Rhode Island RTK

Barium carbonate (CAS 513-77-9)

Crystalline silica (CAS 14808-60-7)

Dolomite (CAS 16389-88-1)

Kaolin (CAS 1332-58-7)

Titanium oxide (CAS 13463-67-7)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)

Titanium oxide (CAS 13463-67-7)

Listed: October 1, 1988

Listed: September 2, 2011

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Listed: February 27, 1987

Inventory status

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)NoCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes


#28953 Page: 10 of 11 Issue date 14-February-2018

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH *	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	Х



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 14-February-2018

Version # 0

Effective date 14-February-2018

Prepared by Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Other information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the

document.