

SAFFTY DATA SHEET

1. Product and Company Identification

Product identifier

651T Misty Mountain Blue

Other means of identification

Not available

Recommended use

Glazing pottery

Recommended restrictions

None known

Manufacturer information

Tucker's Pottery Supplies Inc.,

Cone Art Kilns Inc.

15 West Pearce Street Richmond Hill, ON L4B 1H6 CA

Phone: Toll Free 1-800-304-6185

Phone: 905-889-7705

Emergency Phone Number 613-996-6666 (CANUTEC)

Supplier

See above

2. Hazards Identification

Physical hazards

Not classified.

Health hazards

Serious eye damage/eye irritation

Category 2

Sensitization, respiratory

Category 1

Sensitization, skin

Category 1

Carcinogenicity

Category 1A

Specific target organ toxicity, single exposure

Category 3 respiratory tract irritation

Specific target organ toxicity, repeated

Category 1

exposure

WHMIS 2015 defined hazards

Environmental hazards

Label elements

Not classified. Not classified





Signal word

Danger

Hazard statement

Causes serious eye irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust. Contaminated work clothing should not be allowed out of the workplace. Wear respiratory protection. Use only outdoors or in a well-ventilated area.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see information on this label). Take off contaminated clothing

and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing

respiratory symptoms: Call a POISON CENTER/doctor IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER/doctor if you feel unwell

Storage Disposal Store in a well-ventilated place. Keep container tightly closed. Store locked up.

WHMIS 2015: Health Hazard(s)

not otherwise classified

(HHNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations

None known

WHMIS 2015: Physical Hazard(s) not otherwise

classified (PHNOC)

Hazard(s) not otherwise classified (HNOC)

None known.

None known

Supplemental information

None.

3. Comi	oosition/L	nformation	on Ingredients

ixture			
hemical name	Common name and synonyms	CAS number	%
Feldspar		68476-25-5	52
Crystalline silica		14808-60-7	14
Limestone		1317-65-3	11
Nepheline syenite		37244-96-5	6
Carbonic acid, magnesium sa (1:1)	lt	546-93-0	5
Kaolin		1332-58-7	4
Olivine, Cobalt Silicate Blue		68187-40-6	4
Chemical frits	in the second se	65997-18-4	3
Titanium oxide	22	13463-67-7	0.2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4	Fir	rst	Δi	dΝ	/le	ası	ıres

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing

respiratory symptoms: Call a POISON CENTER or doctor/physician.

Skin contact IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Specific treatment (see information on this label). Take off contaminated clothing

and wash it before reuse.

Eve contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing.

Obtain medical attention.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed General information

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

Hazardous combustion products

May include and are not limited to: Oxides of carbon. Hydrofluoric acid. Silicon tetrafluoride.

#28988 Page: 2 of 13 Issue date 21-February-2018

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Minimize dust generation and accumulation. Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Avoid prolonged exposure. Wear appropriate personal protective equipment. Should be handled in closed systems, if possible. Wash thoroughly after handling. Observe good industrial hygiene practices. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Crystalline silica (CAS

14808-60-7)

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)				
Components	Туре	Value	Form	
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.	
Limestone (CAS 1317-65-3)	TWA	10 mg/m3		
Olivine, Cobalt Silicate Blue (CAS 68187-40-6)	TWA	0.02 mg/m3		
Titanium oxide (CAS 13463-	TWA	10 mg/m3		

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and

Safety Regulation 296/97, as amen		Value	Form
Components	Туре	Agine	101111
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.
Limestone (CAS 1317-65-3)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3 10 mg/m3	Respirable fraction. Total dust.
Olivine, Cobalt Silicate Blue CAS 68187-40-6)	TWA	0.02 mg/m3	
Titanium oxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Canada. Manitoba OELs (Reg. 217	/2006, The Workplace Safety	And Health Act)	
Components	Туре	Value	Form

#28988 Page: 3 of 13 Issue date 21-February-2018

TWA

Respirable fraction.

0.025 mg/m3

Canada. Manitoba OELs (Reg. 217/2006, Components	The Workplace Safety And Health Ac Type	t) Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Olivine, Cobalt Silicate Blue (CAS 68187-40-6)	TWA	0,02 mg/m3	
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Control of Expos Components	eure to Biological or Chemical Agents	s) Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Nepheline syenite (CAS 37244-96-5)	TWA	10 mg/m3	Total dust.
Olivine, Cobalt Silicate Blue (CAS 68187-40-6)	TWA	0.02 mg/m3	
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (Ministry of Labo Components	r - Regulation Respecting the Quality Type	of the Work En	vironment) Form
Carbonic acid, magnesium salt (1:1) (CAS 546-93-0)	TWA	10 mg/m3	Total dust.
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.
imestone (CAS 1317-65-3)	TWA	10 mg/m3	Total dust.
Dlivine, Cobalt Silicate Blue CAS 68187-40-6)	TWA	0.02 mg/m3	
Fitanium oxide (CAS 13463- 67-7)	TWA	10 mg/m3	Total dust.
US. OSHA Table Z-1 Limits for Air Contar Components	ninants (29 CFR 1910.1000) Type	Value	Form
Carbonic acid, magnesium ealt (1:1) (CAS 546-93-0)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Crystalline silica (CAS 4808-60-7)	PEL	0.05 mg/m3	Respirable dust.
(aolin (CAS 1332-58-7)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Limestone (CAS 1317-65-3)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Fitanium oxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
JS. OSHA Table Z-3 (29 CFR 1910.1000) Components	Туре	Value	Form
Crystalline silica (CAS	TWA	0.1 mg/m3	Respirable.
4808-60-7)		2.4 mppcf	Respirable.
(aolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
	TWA	15 mppcf 5 mg/m3	Respirable fraction. Respirable fraction.
	1000		
Fitanium oxide (CAS 13463-67-7)	IVVA	15 mg/m3	Total dust.
	IVVA	15 mg/m3 50 mppcf	Total dust. Total dust.

Components	Туре	Valu	e	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025	5 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg	/m3	Respirable fraction.
Olivine, Cobalt Silicate Blue (CAS 68187-40-6)	TWA	0.02	mg/m3	
Titanium oxide (CAS 13463-67-7)	TWA	10 m	ıg/m3	
US. NIOSH: Pocket Guide Components	to Chemical Hazards Type	Valu	e	Form
Carbonic acid, magnesium	TWA	5 mg		Respirable.
salt (1:1) (CAS 546-93-0)	1 4 4/4	~	ng/m3	Total
Crystalline silica (CAS 14808-60-7)	TWA	0.05	mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	TWA	5 mg	-	Respirable.
			ng/m3	Total
Limestone (CAS 1317-65-3)) TWA	5 mg 10 m	g/m3 ng/m3	Respirable. Total
logical limit values				
ACGIH Biological Exposur Components	re Indices Value Determinar	nt Specimen S	Sampling T	ime
Olivine, Cobalt Silicate Blue (CAS 68187-40-6)	15 μg/l Cobalt	Urine	*	
(CAS 68187-40-6)	15 μg/l Cobalt ase see the source document.	Urine	*	
(CAS 68187-40-6)	10 Fg.	ce dust (total and respir		espirable crystalline silica
(CAS 68187-40-6) * - For sampling details, plea	ase see the source document. Occupational exposure to nuisand	ce dust (total and respired. y 10 air changes per ho If applicable, use proce naintain airborne levels	rable) and re our) should b ess enclosu below recoi	pe used. Ventilation rates res, local exhaust ventilatior mmended exposure limits. It
(CAS 68187-40-6) * - For sampling details, plea posure guidelines propriate engineering atrols	ase see the source document. Occupational exposure to nuisand should be monitored and controlled. Good general ventilation (typically should be matched to conditions or other engineering controls to mexposure limits have not been estimated.	ce dust (total and respired. y 10 air changes per ho If applicable, use proce naintain airborne levels tablished, maintain airb	rable) and re our) should b ess enclosu below recoi	pe used. Ventilation rates res, local exhaust ventilatior mmended exposure limits. It
(CAS 68187-40-6) * - For sampling details, plea posure guidelines propriate engineering atrols	ase see the source document. Occupational exposure to nuisand should be monitored and controlled Good general ventilation (typically should be matched to conditions, or other engineering controls to mexposure limits have not been es	ce dust (total and respired. y 10 air changes per ho If applicable, use proce naintain airborne levels tablished, maintain airb	rable) and re our) should b ess enclosu below recoi	pe used. Ventilation rates res, local exhaust ventilatior mmended exposure limits. It
(CAS 68187-40-6) * - For sampling details, plea posure guidelines propriate engineering atrols ividual protection measures	ase see the source document. Occupational exposure to nuisand should be monitored and controlled. Good general ventilation (typically should be matched to conditions or other engineering controls to mexposure limits have not been estimated.	ce dust (total and respired. y 10 air changes per ho If applicable, use proce naintain airborne levels tablished, maintain airb	rable) and re our) should b ess enclosu below recoi	pe used. Ventilation rates res, local exhaust ventilatior mmended exposure limits. It
(CAS 68187-40-6) * - For sampling details, pleasosure guidelines propriate engineering atrols ividual protection measures Eye/face protection	ase see the source document. Occupational exposure to nuisand should be monitored and controlle Good general ventilation (typically should be matched to conditions, or other engineering controls to mexposure limits have not been estimated as personal protective equitive and we safety glasses with side shift impervious gloves. Confirm with	ce dust (total and respired. y 10 air changes per hone in a process and the process are the process and the process are the process and the process are the p	rable) and re our) should bess enclosu below record orne levels	pe used. Ventilation rates res, local exhaust ventilatior mmended exposure limits. It to an acceptable level.
(CAS 68187-40-6) * - For sampling details, pleasosure guidelines propriate engineering atrols ividual protection measures Eye/face protection	Occupational exposure to nuisand should be monitored and controlled Good general ventilation (typically should be matched to conditions, or other engineering controls to mexposure limits have not been estable safety glasses with side ships of the source of the safety glasses with side ships of the source of the safety glasses with side ships of the safety glasses with side safety glasses with	ce dust (total and respired. y 10 air changes per hone in a process and the process are the process and the process are the process and the process are the p	rable) and re our) should bess enclosu below record orne levels	pe used. Ventilation rates res, local exhaust ventilatior mmended exposure limits. It to an acceptable level.
(CAS 68187-40-6) * - For sampling details, pleasoure guidelines propriate engineering atrols ividual protection measures Eye/face protection Hand protection	ase see the source document. Occupational exposure to nuisand should be monitored and controlle Good general ventilation (typically should be matched to conditions, or other engineering controls to mexposure limits have not been estimated as personal protective equitive as safety glasses with side shift impervious gloves. Confirm with Wear appropriate chemical resist	ce dust (total and respired. y 10 air changes per ho If applicable, use proce naintain airborne levels tablished, maintain airb ipment ields (or goggles). reputable supplier first. ant clothing. Use of an may be exceeded, use and used under the directs found in OSHA's res	rable) and repure should be seen closure below reconstruction of a respirator standard rection and rec	pe used. Ventilation rates res, local exhaust ventilation mmended exposure limits. If to an acceptable level. apron is recommended. As ed NIOSH respirator. trained health and safety adard (29 CFR 1910.134),
(CAS 68187-40-6) * - For sampling details, pleasoure guidelines propriate engineering atrols ividual protection measures Eye/face protection Skin protection Hand protection Other	ase see the source document. Occupational exposure to nuisand should be monitored and controlle Good general ventilation (typically should be matched to conditions, or other engineering controls to mexposure limits have not been estended in the safety glasses with side shift was a safety glasses with side shift was appropriate chemical resist required by employer code. Where exposure guideline levels Respirator should be selected by professional following requirement.	ce dust (total and respired. y 10 air changes per ho If applicable, use proce naintain airborne levels tablished, maintain airb ipment ields (or goggles). reputable supplier first. ant clothing. Use of an may be exceeded, use and used under the directs found in OSHA's res	rable) and repure should be seen closure below reconstruction of a respirator standard rection and rec	pe used. Ventilation rates res, local exhaust ventilation mmended exposure limits. If to an acceptable level. apron is recommended. As ed NIOSH respirator. trained health and safety adard (29 CFR 1910.134),

9. Physical and Chemical Properties			
Appearance	Powder.		
Physical state	Solid.		
Form	Powder.		
Color	grey		

Color grey
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Pour pointNot available.Specific gravityNot available.Partition coefficientNot available.

(n-octanol/water)

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%) Vapor pressure

Not available.

Vapor density

Relative density

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

Decomposition temperature Viscosity

Not available.

Not available:

Other information

Explosive properties
Oxidizing properties

Not explosive. Not oxidizing.

10. Stability and Reactivity

Reactivity

This product may react with strong oxidizing agents.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Chemical stability Material is stable under normal conditions.

Conditions to avoid Contact with incompatible materials. Do not mix with other chemicals,

Incompatible materials

Hazardous decomposition

products

Acids. Powerful oxidizers. Fluorine. Chlorine.

May include and are not limited to: Oxides of carbon. Silicon tetrafluoride. Hydrofluoric acid.

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion

May cause stomach distress, nausea or vomiting.

Inhalation

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Dust may irritate respiratory

system.

Skin contact

Dust or powder may irritate the skin. May cause an allergic skin reaction.

Eye contact

Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Difficulty in breathing.

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

May cause respiratory irritation. May cause an allergic skin reaction.

Components

Species

Test Results

Carbonic acid, magnesium salt (1:1) (CAS 546-93-0)

Acute

Dermal

LD50

Not available

Inhalation

LC50

Not available

#28988 Page: 6 of 13 Issue date 21-February-2018

Components **Species Test Results** Oral LD50 Not available > 2000 mg/kg, ECHA Rat Chemical frits (containing lead) (CAS 65997-18-4) **Acute** Dermal LD50 Rat > 2000 mg/kg, 24 Hours Inhalation LC50 Mouse > 9 mg/m3, 15 Minutes, ECHA Mouse, Rat > 1 mg/m3, 3 Hours, ECHA Rabbit > 22.4 mg/m3, 15 Minutes, ECHA > 4.5 mg/m3, 2 Hours, ECHA Rat > 8.6 mg/m3, 30 Minutes, ECHA > 4.6 mg/m3, 3 Hours, ECHA > 4.5 mg/m3, 2 Hours, ECHA > 1.9 mg/L, 4 Hours, ECHA 112 mg/m3, 2 Hours, ECHA 4.4 mg/L, 4 Hours, ECHA 2.2 mg/L, 4 Hours, ECHA Oral LD50 Mouse 890 mg/kg, ECHA 63 mg/kg, ECHA Mouse, Rat 41 mg/kg, ECHA 7.7 mg/kg, ECHA Rat > 11000 mg/kg, ECHA > 5000 mg/kg, ECHA > 2000 mg/kg, ECHA 63 - 259 mg/kg, ECHA 9990 mg/kg, ECHA 8796 mg/kg, ECHA 2330 mg/kg, ECHA 314 mg/kg, ECHA 300 - 2000 mg/kg, ECHA 221 mg/kg, ECHA Crystalline silica (CAS 14808-60-7) Acute Dermal LD50 Not available Inhalation LC50 Not available Oral LD50 Rat 500 mg/kg, HSDB, IV only Feldspar (CAS 68476-25-5) Acute Dermal LD50 Not available Inhalation LC50 Not available Oral LD50 Not available

Components **Species Test Results** Kaolin (CAS 1332-58-7) **Acute** Dermal LD50 Rat > 5000 mg/kg, HSDB Inhalation LC50 Not available Oral LD50 Rat > 5000 mg/kg, HSDB 14900 mg/kg, Gelest Limestone (CAS 1317-65-3) **Acute** Dermal LD50 Not available Inhalation LC50 Not available Oral LD50 Rat 6450 mg/kg, SPI Pharma Nepheline syenite (CAS 37244-96-5) Acute Dermal LD50 Not available Inhalation LC50 Not available Oral LD50 Not available Olivine, Cobalt Silicate Blue (CAS 68187-40-6) Acute Dermal LD50 Not available Inhalation LC50 Rat > 5.3 mg/L, 4 Hours, ECHA Oral LD50 Rat > 2000 mg/kg, ECHA 1830 mg/kg, ECHA 1630 mg/kg, ECHA 1480 mg/kg, ECHA Titanium oxide (CAS 13463-67-7) Acute Dermal LD50 Not available Inhalation LC50 Rat > 6.8 mg/L, 4 Hours, ECHA > 3.6 mg/l/4h, ECHA > 3.6 mg/L, 4 Hours, ECHA > 2.3 mg/L, 4 Hours, ECHA 5.1 mg/L, 4 Hours, ECHA 3.4 mg/L, 4 Hours, ECHA Oral LD50 Mouse > 5000 mg/kg, ECHA Rat > 25000 mg/kg, ECHA > 11000 mg/kg, ECHA > 5000 mg/kg, ECHA

Test Results Components Species

> 2000 mg/kg, ECHA

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation

Not available. **Exposure minutes** Not available. Erythema value

Oedema value Not available.

Serious eye damage/eye irritation

Causes serious eye irritation.

Not available. Corneal opacity value Iris lesion value Not available.

Not available. Conjunctival reddening value

Conjunctival oedema value Not available. Not available. Recover days

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Irritant Cristobalite (CAS 14464-46-1) Limestone (CAS 1317-65-3) Irritant Irritant Titanium oxide (CAS 13463-67-7)

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory sensitization

May cause an allergic skin reaction. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Mutagenicity

mutagenic or genotoxic.

May cause cancer. Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce

the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently

assured by respecting the existing regulatory occupational exposure limits.

Occupational exposure to respirable dust and respirable crystalline silica should be monitored and

controlled. High concentrations of pigment-grade (powdered) and ultrafine titanium dioxide (titanium oxide)

dust have caused respiratory tract cancer in rats exposed by inhalation and intratracheal

instillation.

ACGIH Carcinogens

A2 Suspected human carcinogen. Cristobalite (CAS 14464-46-1) Crystalline silica (CAS 14808-60-7) A2 Suspected human carcinogen.

A3 Confirmed animal carcinogen with unknown relevance to Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

humans

Canada - Alberta OELs: Carcinogen category

Suspected human carcinogen. Cristobalite (CAS 14464-46-1) Suspected human carcinogen. Crystalline silica (CAS 14808-60-7)

Canada - Manitoba OELs: carcinogenicity

Cobalt and inorganic compounds, as Co (CAS

68187-40-6)

SILICA, CRYSTALLINE-ALPHA -QUARTZ, RESPIRABLE FRACTION (CAS 14808-60-7)

SILICA, CRYSTALLINE-CRISTOBALITE, RESPIRABLE

FRACTION (CAS 14464-46-1)

Suspected human carcinogen. Suspected human carcinogen.

Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

Detected carcinogenic effect in animals. Cristobalite (CAS 14464-46-1) Suspected carcinogenic effect in humans. Crystalline silica (CAS 14808-60-7) Detected carcinogenic effect in animals. Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1)

Crystalline silica (CAS 14808-60-7)

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

Volume 68, Volume 100C 1 Carcinogenic to humans.

Volume 68, Volume 100C 1 Carcinogenic to humans.

Volume 52 - 2B Possibly carcinogenic to humans.

Titanium oxide (CAS 13463-67-7) Volume 47, Volume 93 - 2B Possibly carcinogenic to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7) Titanium oxide (CAS 13463-67-7)

US NTP Report on Carcinogens: Anticipated carcinogen

Cristobalite (CAS 14464-46-1) Reasonably Anticipated to be a Human Carcinogen.

US NTP Report on Carcinogens: Known carcinogen

Cristobalite (CAS 14464-46-1)

Crystalline silica (CAS 14808-60-7)

Known To Be Human Carcinogen.

Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Cristobalite (CAS 14464-46-1) Cancer Crystalline silica (CAS 14808-60-7) Cancer

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Teratogenicity Not available.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects. Prolonged or repeated exposure to fine airborne crystalline silica dust may cause severe scarring of the lungs, a disease called silicosis. Early symptoms of silicosis include cough, mucous production and shortness of breath upon

exertion.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components Species Test Results

Titanium oxide (CAS 13463-67-7)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/L, 48 hours
Fish LC50 Mummichog (Fundulus heteroclitus) > 1000 mg/L, 96 hours

No data is available on the degradability of this product.

Persistence and degradability

Bioaccumulative potentialNo data available.Mobility in soilNo data available.Mobility in generalNot available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispo

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification

In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

#28988 Page: 10 of 13 Issue date 21-February-2018

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Cristobalite (CAS 14464-46-1) Listed.
Kaolin (CAS 1332-58-7) Listed.
Titanium oxide (CAS 13463-67-7) Listed.

Canada DSL Challenge Substances: Listed substance

Cristobalite (CAS 14464-46-1) Listed.
Crystalline silica (CAS 14808-60-7) Listed.
Canada Priority Substances List (Second List): Listed substance

Kaolin (CAS 1332-58-7) Listed. Titanium oxide (CAS 13463-67-7) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Olivine, Cobalt Silicate Blue (CAS 68187-40-6) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Cristobalite (CAS 14464-46-1)
Crystalline silica (CAS 14808-60-7)
Cristobalite (CAS 14464-46-1)
Crystalline silica (CAS 14808-60-7)
Lung effects
Crystalline silica (CAS 14808-60-7)

Cristobalite (CAS 14464-46-1) immune system effects
Crystalline silica (CAS 14808-60-7) immune system effects
Cristobalite (CAS 14464-46-1) kidney effects

Cristobalite (CAS 14464-46-1) kidney effects
Crystalline silica (CAS 14808-60-7) kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

No

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

See below

US - California Hazardous Substances (Director's): Listed substance

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

Listed.

US - Illinois Chemical Safety Act: Listed substance

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

#28988 Page: 11 of 13 Issue date 21-February-2018

US - Louisiana Spill Reporting: Listed substance

Olivine, Cobalt Silicate Blue (CAS 68187-40-6) Listed.

US - Minnesota Haz Subs: Listed substance

Carbonic acid, magnesium salt (1:1) (CAS 546-93-0) Listed. Cristobalite (CAS 14464-46-1) Listed. Crystalline silica (CAS 14808-60-7) Listed. Kaolin (CAS 1332-58-7) Listed. Limestone (CAS 1317-65-3) Listed. Olivine, Cobalt Silicate Blue (CAS 68187-40-6) Listed. Titanium oxide (CAS 13463-67-7) Listed.

US - New Jersey RTK - Substances: Listed substance

Carbonic acid, magnesium salt (1:1) (CAS 546-93-0)

Cristobalite (CAS 14464-46-1)

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7) Limestone (CAS 1317-65-3)

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

Titanium oxide (CAS 13463-67-7)

US - Texas Effects Screening Levels: Listed substance

Carbonic acid, magnesium salt (1:1) (CAS 546-93-0) Listed Chemical frits (containing lead) (CAS 65997-18-4) Listed. Cristobalite (CAS 14464-46-1) Listed. Crystalline silica (CAS 14808-60-7) Listed. Feldspar (CAS 68476-25-5) Listed. Kaolin (CAS 1332-58-7) Listed. Limestone (CAS 1317-65-3) Listed. Nepheline syenite (CAS 37244-96-5) Listed. Titanium oxide (CAS 13463-67-7) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

US. Massachusetts RTK - Substance List

Carbonic acid, magnesium salt (1:1) (CAS 546-93-0)

Cristobalite (CAS 14464-46-1)

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium oxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Cristobalite (CAS 14464-46-1)

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Olivine, Cobalt Silicate Blue (CAS 68187-40-6)

Titanium oxide (CAS 13463-67-7)

US. Rhode Island RTK

Carbonic acid, magnesium salt (1:1) (CAS 546-93-0)

Cristobalite (CAS 14464-46-1)

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium oxide (CAS 13463-67-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)

Listed: October 1, 1988

Titanium oxide (CAS 13463-67-7)

Listed: September 2, 2011

Inventory status

#28988

Country(s) or region Inventory name On inventory (yes/no)*

Canada Domestic Substances List (DSL)

No Yes

Issue date 21-February-2018

Canada
United States & Puerto Rico

Non-Domestic Substances List (NDSL)

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)


Page: 12 of 13

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Disclaimer





The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

21-February-2018

01

Issue date Version #

Effective date

Prepared by

Other information

21-February-2018

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.