

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier

Other means of identification

Recommended use

Recommended restrictions

Manufacturer information

657T Melted Moss

Not available

Glazing pottery

None known.

Tucker's Pottery Supplies Inc.,

Cone Art Kilns Inc. 15 West Pearce Street

Richmond Hill, ON L4B 1H6 CA Phone: Toll Free 1-800-304-6185

Phone: 905-889-7705

Emergency Phone Number: 613-996-6666 (CANUTEC)

Supplier See above

2. Hazards Identification

Physical hazards

Not classified.

Health hazards

Sensitization, respiratory

Sensitization, skin

Category 1

Carcinogenicity

Category 1A

Category 1

Reproductive toxicity

Category 1 Category 1

Specific target organ toxicity, repeated

exposure

WHMIS 2015 defined hazards

Environmental hazards

Label elements

Not classified. Not classified



Signal word

Hazard statement

Danger

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause cancer. May damage fertility or the unborn child. Causes damage

to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Do not breathe dust. Contaminated work clothing should not be allowed out of the workplace Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood.

Response

IF ON SKIN: Wash with plenty of water, If skin irritation or rash occurs: Get medical

advice/attention. Specific treatment (see information on this label). Take off contaminated clothing

and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing

respiratory symptoms: Call a POISON CENTER/doctor

IF exposed or concerned: Get medical advice/attention.

Page: 1 of 11

Get medical advice/attention if you feel unwell.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

WHMIS 2015: Health Hazard(s)

not otherwise classified

(HHNOC)

#28973

WHMIS 2015: Physical

Hazard(s) not otherwise classified (PHNOC)

None known

None known

Hazard(s) not otherwise

classified (HNOC)

None known

Issue date 16-February-2018

Mixture			
Chemical name	Common name and synonyms	CAS number	%
Nepheline syenite		37244-96-5	38
Crystalline silica		14808-60-7	18
Calcium Tetraborate		12007-56-6	12
Kaolin		1332-58-7	10
Leucoxene		103170-28-1	3.8
Rutile		1317-80-2	3.8
Tricobalt Tetraoxide		1308-06-1	1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing

respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical Skin contact

advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see

information on this label).

Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical Eye contact

attention if irritation persists.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to

reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing.

Obtain medical attention:

Most important symptoms/effects, acute and

delayed Indication of immediate medical attention and special

treatment needed General information Dusts may irritate the respiratory tract, skin and eyes. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire-fiahtina equipment/instructions

Specific methods General fire hazards

Hazardous combustion products

Water fog. Foam. Dry chemical powder. Carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

May include and are not limited to: Silicon tetrafluoride. Hydrofluoric acid.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Minimize dust generation and accumulation. Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Wear appropriate personal protective equipment. Should be handled in closed systems, if possible. Wash thoroughly after handling. Observe good industrial hygiene practices. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada, Alberta OELs	(Occupational Health & Safet	y Code, Schedule 1, Table 2)
----------------------	------------------------------	------------------------------

Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.
Rutile (CAS 1317-80-2)	TWA	10 mg/m3	
Tricobalt Tetraoxide (CAS 1308-06-1)	TWA	0.02 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components Type		Value	Form	
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.	
Rutile (CAS 1317-80-2)	TWA	3 mg/m3 10 mg/m3	Respirable fraction, Total dust.	
Tricobalt Tetraoxide (CAS 1308-06-1)	TWA	0.02 mg/m3		

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
Calcium Tetraborate (CAS 12007-56-6)	STEL	6 mg/m3	Inhalable fraction.
	TWA	2 mg/m3	Inhalable fraction.
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Rutile (CAS 1317-80-2)	TWA	10 mg/m3	
Tricobalt Tetraoxide (CAS 1308-06-1)	TWA	0.02 mg/m3	

Canada, Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Calcium Tetraborate (CAS 12007-56-6)	STEL	6 mg/m3	Inhalable fraction.
	TWA	2 mg/m3	Inhalable fraction.
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction,

Components	Туре			Value	Form
Kaolin (CAS 1332-58-7)	TWA		2	2 mg/m3	Respirable fraction.
Nepheline syenite (CAS 37244-96-5)	TWA		,	10 mg/m3	Total dust.
Rutile (CAS 1317-80-2)	TWA		•	10 mg/m3	
Tricobalt Tetraoxide (CAS 1308-06-1)	TWA		(0.02 mg/m3	
Canada. Quebec OELs. (M Components	inistry of Labor - Regu Type	lation Respecting		of the Work Environ Value	nment) Form
Crystalline silica (CAS 14808-60-7)	TWA		(0.1 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	TWA		;	5 mg/m3	Respirable dust.
Rutile (CAS 1317-80-2)	TWA			10 mg/m3	Total dust.
Tricobalt Tetraoxide (CAS 1308-06-1)	TWA		(0.02 mg/m3	
US. OSHA Table Z-1 Limits Components	s for Air Contaminants Type	(29 CFR 1910.10		Value	Form
Crystalline silica (CAS 14808-60-7)	PEL			0.05 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	PEL			5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Rutile (CAS 1317-80-2)	PEL			15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 Cl Components	FR 1910.1000) Type			Value	Form
Crystalline silica (CAS	TWA			0.1 mg/m3	Respirable.
14808-60-7)				2.4 mppcf	Respirable.
Kaolin (CAS 1332-58-7)	TWA			5 mg/m3 15 mg/m3 50 mppcf 15 mppcf	Respirable fraction, Total dust. Total dust. Respirable fraction,
US. ACGIH Threshold Limi Components	it Values Type			Value	Form
Calcium Tetraborate (CAS 12007-56-6)	STEL			6 mg/m3	Inhalable fraction.
	TWA			2 mg/m3	Inhalable fraction.
Crystalline silica (CAS 14808-60-7)	TWA			0.025 mg/m3	Respirable fraction,
Kaolin (CAS 1332-58-7)	TWA			2 mg/m3	Respirable fraction
Rutile (CAS 1317-80-2)	TWA			10 mg/m3	
Tricobalt Tetraoxide (CAS 1308-06-1)	TWA			0.02 mg/m3	
US. NIOSH: Pocket Guide Components	to Chemical Hazards Type			Value	Form
Crystalline silica (CAS 14808-60-7)	TWA			0.05 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	TWA			5 mg/m3 10 mg/m3	Respirable. Total
ogical limit values					
ACGIH Biological Exposur Components	re Indices Value	Determinant	Specimen	Sampling Time	
Tricobalt Tetraoxide (CAS	15 μg/l	Cobalt	Urine	*	

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. $\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left($

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation. or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Impervious gloves. Confirm with reputable supplier first.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As

required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134),

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance Physical state Powder. Solid.

Form Color Odor Powder. Beige. Odorless

Odor threshold

Not available. Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling

range

Not available.

Pour point

Not available.

Specific gravity

Not available.

Partition coefficient (n-octanol/water)

Not available.

Flash point

Not available. Not available.

Evaporation rate Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure Vapor density

Not available. Not available.

Relative density

Not available.

Solubility(ies) Auto-ignition temperature Not available. Not available.

Decomposition temperature

Not available. Not available.

Other information

Explosive properties Oxidizing properties

Not explosive.

Not oxidizing.

10. Stability and Reactivity

Reactivity

Viscosity

This product may react with strong oxidizing agents.

Issue date 16-February-2018 #28973 Page: 5 of 11

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Chemical stability

Material is stable under normal conditions.

Conditions to avoid

Do not mix with other chemicals.

Incompatible materials Hazardous decomposition Powerful oxidizers. Chlorine.

products

May include and are not limited to: Silicon tetrafluoride. Hydrofluoric acid,

11. Toxicological Information

Routes of exposure

Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion

May cause stomach distress, nausea or vomiting.

Inhalation

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Dust may irritate respiratory

system.

Skin contact

Dust or powder may irritate the skin. May cause an allergic skin reaction.

Eye contact

Dust may irritate the eyes.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes. Difficulty in breathing. May cause an

allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

May cause an allergic skin reaction.

Components

Species

Test Results

Calcium Tetraborate (CAS 12007-56-6)

Acute

Dermal

LD50

Not available

Inhalation

LC50

Not available

Oral

LD50

Not available

Crystalline silica (CAS 14808-60-7)

Acute

Dermal

LD50

Not available

Inhalation

LC50

Not available

Oral

LD50

Rat

500 mg/kg, HSDB, IV only

Kaolin (CAS 1332-58-7)

Acute

Dermal

LD50

Rat

> 5000 mg/kg, HSDB

Inhalation

LC50

Not available

Oral

LD50

Rat

> 5000 mg/kg, HSDB

14900 mg/kg, Gelest

Nepheline syenite (CAS 37244-96-5)

Acute

Dermal

LD50

Not available

Inhalation

LC50

Not available

Test Results Species Components Oral LD50 Not available Rutile (CAS 1317-80-2) Acute Demal LD50 Not available Inhalation > 6.8 mg/L, 4 Hours, ECHA LC50 Rat > 3.6 mg/L, 4 Hours, ECHA > 2.3 mg/L, 4 Hours, ECHA 5.1 mg/L, 4 Hours, ECHA 3.4 mg/L, 4 Hours, ECHA Oral LD50 Rat > 25000 mg/kg, ECHA > 11000 mg/kg, ECHA > 5000 mg/kg, ECHA > 2000 mg/kg, ECHA Tricobalt Tetraoxide (CAS 1308-06-1) Acute Dermal > 2000 mg/kg, 24 Hours, ECHA LD50 Rat Inhalation > 5.1 mg/L, 4 Hours, ECHA LC50 Rat Oral > 5000 mg/kg, ECHA LD50 Rat Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Not available. **Exposure minutes** Not available. Erythema value Not available. Oedema value Direct contact with eyes may cause temporary irritation. Serious eye damage/eye irritation Not available. Corneal opacity value Not available. Iris lesion value Not available. Conjunctival reddening value Not available. Conjunctival oedema value Recover days Not available. Respiratory or skin sensitization Canada - Alberta OELs: Irritant Irritant Rutile (CAS 1317-80-2) Irritant Titanium oxide (CAS 13463-67-7) May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory sensitization May cause an allergic skin reaction. Skin sensitization No data available to indicate product or any components present at greater than 0.1% are Mutagenicity mutagenic or genotoxic.

Carcinogenicity

May cause cancer.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs," (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis.

"There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce

the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently

assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and

controlled.

ACGIH Carcinogens

Crystalline silica (CAS 14808-60-7)

A2 Suspected human carcinogen.

Tricobalt Tetraoxide (CAS 1308-06-1) A3 Confirmed animal carcinogen with unknown relevance to

humans

Canada - Alberta OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7)

Suspected human carcinogen.

Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Cobalt and inorganic compounds, as Co (CAS

1308-06-1)

Confirmed animal carcinogen with unknown relevance to humans.

SILICA, CRYSTALLINE-ALPHA.-QUARTZ, RESPIRABLE FRACTION (CAS 14808-60-7)

Canada - Quebec OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7) Tricobalt Tetraoxide (CAS 1308-06-1) Suspected carcinogenic effect in humans,

Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (CAS 14808-60-7)

Rutile (CAS 1317-80-2)

Volume 68, Volume 100C 1 Carcinogenic to humans. Volume 47, Volume 93 - 2B Possibly carcinogenic to humans.

Titanium oxide (CAS 13463-67-7) Tricobalt Tetraoxide (CAS 1308-06-1)

Volume 47, Volume 93 - 2B Possibly carcinogenic to humans.

Volume 52 - 2B Possibly carcinogenic to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)

Rutile (CAS 1317-80-2)

Titanium oxide (CAS 13463-67-7)

US NTP Report on Carcinogens: Known carcinogen

Crystalline silica (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7)

Reproductive toxicity

May damage fertility or the unborn child.

Teratogenicity

Not available.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Causes damage to organs through prolonged or repeated exposure.

Prolonged inhalation may be harmful.

Prolonged or repeated exposure to fine airborne crystalline silica dust may cause severe scarring of the lungs, a disease called silicosis. Early symptoms of silicosis include cough, mucous

production and shortness of breath upon exertion.

12. Ecological Information

See below **Ecotoxicity**

Ecotoxicological data

Components

Species

Test Results

Rutile (CAS 1317-80-2)

Aquatic

Crustacea

EC50

Water flea (Daphnia magna)

> 1000 mg/L, 48 hours

#28973 Page: 8 of 11 Issue date 16-February-2018 Components

Species

Test Results

Fish

LC50

Mummichog (Fundulus heteroclitus)

No data is available on the degradability of this product.

> 1000 mg/L, 96 hours

Persistence and degradability

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Mobility in general

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

Contaminated packaging

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification

In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue,

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Kaolin (CAS 1332-58-7)

Listed.

Titanium oxide (CAS 13463-67-7)

Crystalline silica (CAS 14808-60-7)

Canada DSL Challenge Substances: Listed substance

Listed.

Canada Priority Substances List (Second List): Listed substance

Kaolin (CAS 1332-58-7)

Listed.

Titanium oxide (CAS 13463-67-7)

Listed. Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Tricobalt Tetraoxide (CAS 1308-06-1)

Listed

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7)

Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Nο

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Tricobalt Tetraoxide (CAS 1308-06-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

See below

US - California Hazardous Substances (Director's): Listed substance

Tricobalt Tetraoxide (CAS 1308-06-1)

Listed.

Zircon (CAS 14940-68-2)

Listed.

US - Illinois Chemical Safety Act: Listed substance

Tricobalt Tetraoxide (CAS 1308-06-1)

US - Louisiana Spill Reporting: Listed substance

Tricobalt Tetraoxide (CAS 1308-06-1)

Listed.

US - Minnesota Haz Subs: Listed substance

 Crystalline silica (CAS 14808-60-7)
 Listed.

 Kaolin (CAS 1332-58-7)
 Listed.

 Rutile (CAS 1317-80-2)
 Listed.

 Titanium oxide (CAS 13463-67-7)
 Listed.

 Tricobalt Tetraoxide (CAS 1308-06-1)
 Listed.

 Zircon (CAS 14940-68-2)
 Listed.

US - New Jersey RTK - Substances: Listed substance

Calcium Tetraborate (CAS 12007-56-6) Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7) Rutile (CAS 1317-80-2)

Titanium oxide (CAS 13463-67-7) Tricobalt Tetraoxide (CAS 1308-06-1)

US - Texas Effects Screening Levels: Listed substance

 Crystalline silica (CAS 14808-60-7)
 Listed.

 Kaolin (CAS 1332-58-7)
 Listed.

 Nepheline syenite (CAS 37244-96-5)
 Listed.

 Rutile (CAS 1317-80-2)
 Listed.

 Titanium oxide (CAS 13463-67-7)
 Listed.

 Zircon (CAS 14940-68-2)
 Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Tricobalt Tetraoxide (CAS 1308-06-1)

US. Massachusetts RTK - Substance List

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7) Rutile (CAS 1317-80-2)

Titanium oxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Tricobalt Tetraoxide (CAS 1308-06-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Rutile (CAS 1317-80-2)

Titanium oxide (CAS 13463-67-7)

Tricobalt Tetraoxide (CAS 1308-06-1)

US. Rhode Island RTK

Crystalline silica (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Rutile (CAS 1317-80-2)

Titanium oxide (CAS 13463-67-7) Zircon (CAS 14940-68-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)

Rutile (CAS 1317-80-2)

Titanium oxide (CAS 13463-67-7)

Listed: October 1, 1988

Listed: September 2, 2011 Listed: September 2, 2011

Inventory status

Country(s) or region

Inventory name

On inventory (yes/no)*

Canada

Domestic Substances List (DSL)

No

Canada

Non-Domestic Substances List (NDSL)

No

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory


No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0





Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty. expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

16-February-2018

Version #

01

Effective date

16-February-2018

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the

document.