


SAFETYDATASHEET

1. Product and Company Identification

Product identifier	New Bright White
Other means of identification	Not available
Recommended use	Modelling Clay
Recommended restrictions	None known.
Manufacturer information	Tucker's Pottery Supplies Inc., Cone Art Kilns Inc. 15 West Pearce Street Richmond Hill, ON L4B 1H6 CA Phone: Toll Free 1-800-304-6185 Phone: 905-889-7705 Emergency Phone Number: 613-996-6666 (CANUTEC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Not classified.
Health hazards	Carcinogenicity Category 1A Specific target organ toxicity, repeated exposure Category 1 Not classified.
Environmental hazards	Not classified
WHMIS 2015 defined hazards	
Label elements	
Signal word	Danger
Hazard statement	May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary statement	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.
Prevention	
Response	IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. Store locked up.
Storage	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
WHMIS 2015: Health Hazard(s)	None known
not otherwise classified (HHNOC)	
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Kaolin		1332-58-7	42
Nepheline syenite		37244-96-5	29
Crystalline silica		14808-60-7	24

Chemical name	Common name and synonyms	CAS number	%
Titanium oxide		13463-67-7	0.2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	May include and are not limited to: Silicon tetrafluoride. Hydrofluoric acid.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. When using, do not eat, drink or smoke. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.
Conditions for safe storage, materials including any incompatibilities	Store locked up. Store in original tightly closed container. Store away from incompatible (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2.mg/m3	Respirable.
Titanium oxide (CAS 13463-67-7)	TWA	3.mg/m3	Respirable fraction.
		10 mg/m3	Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
------------	------	-------	------

Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Control of Exposure Components)	re to Biological or Chemical Agents Type) Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Nepheline syenite (CAS 37244-96-5)	TWA	10 mg/m3	Total dust.
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (Ministry of Labor Components)	Regulation Respecting the Quality Type	of the Work Enviro Value	nment) Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Titanium oxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.1000) Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Kaolin (CAS 1332-58-7)	TWA	2.4 mppcf	Respirable.
		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. OSHA Table Z-3 (29 CFR 1910.1000) Components	Type	Value	Form
Titanium oxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards
Components

	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable
Kaolin (CAS 1332-58-7)			
dust.			
	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits.

If exposure limits have not been established, maintain airborne levels to an acceptable level. **Individual protection measures, such as personal protective equipment**

Eye/face protection

Wear safety glasses with side shields.

Skin protection

Hand protection

Impervious gloves. Confirm with reputable supplier first.

Other

Use of an impervious apron is recommended. As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Moist mud
Physical state	Solid.
Form	Solid.
Color	grey
Odor	Earthy
Odor threshold	Not available.
pH	6 - 8
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available. Not available.
Other information Explosive properties	
Oxidizing properties	Not explosive. Not oxidizing.

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Powerful oxidizers. Chlorine.
Hazardous decomposition products	May include and are not limited to: Hydrofluoric acid. Silicon tetrafluoride.

11. Toxicological Information

Routes of exposure Inhalation. Eye, Skin contact, Inhalation, Ingestion. Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may result in mechanical irritation.
Symptoms related to the	Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Crystalline silica (CAS 14808-60-7)		
Acute		
Dermal		
LD50	Not available	
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	500 mg/kg, HSDB, IV only
Kaolin (CAS 1332-58-7)		
Acute		
Dermal	Rat	
LD50		> 5000 mg/kg, HSDB

Components	Species	Test Results
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Rat	> 5000 mg/kg, HSDB
		14900 mg/kg, Gelest
Nepheline syenite (CAS 37244-96-5)		
Acute <i>Dermal</i> LD50	Rat	> 6.8 mg/L, 4 Hours, ECHA
<i>Inhalation</i> LC50		> 3.6 mg/l/4h, ECHA
<i>Oral</i> LD50		> 3.6 mg/L, 4 Hours, ECHA
Titanium oxide (CAS 13463-67-7)		
Acute <i>Dermal</i> LD50		> 2.3 mg/L, 4 Hours, ECHA
<i>Inhalation</i> LC50		5.1 mg/L, 4 Hours, ECHA
		3.4 mg/L, 4 Hours, ECHA
	Mouse	> 5000 mg/kg, ECHA
	Rat	> 25000 mg/kg, ECHA
<i>Oral</i> LD50	Not available	
		> 11000 mg/kg, ECHA
		> 5000 mg/kg, ECHA
Skin corrosion/irritation		> 2000 mg/kg, ECHA
Exposure minutes		
Erythema value		
Oedema value	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Not available.	
	Not available.	
Corneal opacity value	Not available.	
Iris lesion value	Direct contact with eyes may cause temporary irritation.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization	Not available.	
	Not available.	
Not available		
Not available		
Canada - Alberta OELs: Irritant		
Cristobalite (CAS 14464-46-1)		Irritant
Titanium oxide (CAS 13463-67-7)		Irritant

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	May cause cancer.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

12. Ecological Information

Ecotoxicity	See below
--------------------	-----------

High concentrations of pigment-grade (powdered) and ultrafine titanium dioxide (titanium oxide) dust have caused respiratory tract cancer in rats exposed by inhalation and intratracheal instillation.

ACGIH Carcinogens

Cristobalite (CAS 14464-46-1)	A2 Suspected human carcinogen.
Crystalline silica (CAS 14808-60-7)	A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Cristobalite (CAS 14464-46-1)	Suspected human carcinogen.
Crystalline silica (CAS 14808-60-7)	Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

SILICA, CRYSTALLINE-.ALPHA.-QUARTZ, RESPIRABLE FRACTION (CAS 14808-60-7)	Suspected human carcinogen.
SILICA, CRYSTALLINE-CRISTOBALITE, RESPIRABLE FRACTION (CAS 14464-46-1)	Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Cristobalite (CAS 14464-46-1)	Detected carcinogenic effect in animals.
Crystalline silica (CAS 14808-60-7)	Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1)	Volume 68, Volume 100C 1 Carcinogenic to humans.
Crystalline silica (CAS 14808-60-7)	Volume 68, Volume 100C 1 Carcinogenic to humans.
Titanium oxide (CAS 13463-67-7)	Volume 47, Volume 93 - 2B Possibly carcinogenic to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)
Titanium oxide (CAS 13463-67-7)

US NTP Report on Carcinogens: Anticipated carcinogen

Cristobalite (CAS 14464-46-1)	Reasonably Anticipated to be a Human Carcinogen. US NTP Report on
-------------------------------	--

Carcinogens: Known carcinogen

Cristobalite (CAS 14464-46-1)	Known To Be Human Carcinogen. Crystalline silica (CAS 14808-60-7)
Known To Be Human Carcinogen. US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	

Cristobalite (CAS 14464-46-1)	Cancer
Crystalline silica (CAS 14808-60-7)	Cancer

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects. Prolonged or repeated exposure to fine airborne crystalline silica dust may cause severe scarring of the lungs, a disease called silicosis. Early symptoms of silicosis include cough, mucous production and shortness of breath upon exertion.

Ecotoxicological data	Species	> 1000 mg/L, 48 hours
Components		
Titanium oxide (CAS 13463-67-7)		> 1000 mg/L, 96 hours
Aquatic	Water flea (Daphnia magna)	
Crustacea	Mummichog (Fundulus heteroclitus)	
EC50	Test Results	

Fish LC50
Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. **Mobility in soil**
 No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.
U.S. Department of Transportation (DOT)	Not regulated as dangerous goods.
Transportation of Dangerous Goods (TDG - Canada)	Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
Canada CEPA Schedule I: Listed substance	

Cristobalite (CAS 14464-46-1) Listed. Kaolin (CAS 1332-58-7)
Listed.
Titanium oxide (CAS 13463-67-7) Listed.

Canada DSL Challenge Substances: Listed substance

Cristobalite (CAS 14464-46-1) Listed. Crystalline silica (CAS 14808-60-7) Listed.

Canada Priority Substances List (Second List): Listed substance

Kaolin (CAS 1332-58-7) Listed.
Titanium oxide (CAS 13463-67-7) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Cristobalite (CAS 14464-46-1)	Cancer
Crystalline silica (CAS 14808-60-7)	Cancer lung effects
Cristobalite (CAS 14464-46-1)	lung effects immune system effects
Crystalline silica (CAS 14808-60-7)	immune system effects
Cristobalite (CAS 14464-46-1)	kidney effects kidney effects
Crystalline silica (CAS 14808-60-7)	kidney effects
Cristobalite (CAS 14464-46-1)	
Crystalline silica (CAS 14808-60-7)	

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - Minnesota Haz Subs: Listed substance

Cristobalite (CAS 14464-46-1)	Listed.
Crystalline silica (CAS 14808-60-7)	Listed.
Kaolin (CAS 1332-58-7)	Listed.
Titanium oxide (CAS 13463-67-7)	Listed.

US - New Jersey RTK - Substances: Listed substance

Cristobalite (CAS 14464-46-1)
Crystalline silica (CAS 14808-60-7)
Kaolin (CAS 1332-58-7)
Titanium oxide (CAS 13463-67-7)

US - Texas Effects Screening Levels: Listed substance

Cristobalite (CAS 14464-46-1)
 Crystalline silica (CAS 14808-60-7)
 Kaolin (CAS 1332-58-7)
 Nepheline syenite (CAS 37244-96-5)
 Titanium oxide (CAS 13463-67-7)

Listed.
 Listed.
 Listed.
 Listed.
 Listed.

US. Massachusetts RTK - Substance List

Cristobalite (CAS 14464-46-1)
 Crystalline silica (CAS 14808-60-7)
 Kaolin (CAS 1332-58-7)
 Titanium oxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania Worker and Community Right-to-Know Law

Cristobalite (CAS 14464-46-1)
 Crystalline silica (CAS 14808-60-7)
 Kaolin (CAS 1332-58-7)
 Titanium oxide (CAS 13463-67-7)

US. Rhode Island RTK

Cristobalite (CAS 14464-46-1)
 Crystalline silica (CAS 14808-60-7)
 Kaolin (CAS 1332-58-7)
 Titanium oxide (CAS 13463-67-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)	Listed: October 1, 1988
Titanium oxide (CAS 13463-67-7)	Listed: September 2, 2011

Inventory status

Country(s) or region	Inventory name	On inventory(yes/no)*
----------------------	----------------	-----------------------

Canada Domestic Substances List (DSL)	Yes	Canada Non-Domestic Substances List (NDSL)	No
---------------------------------------	-----	--	----

United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory
-----------------------------	---


Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date	07-February-2018
Version #	01
Effective date	07-February-2018
Prepared by	Dell Tech Laboratories Ltd. Phone: (519) 858-5021
Other information	For an updated SDS, please contact the supplier/manufacturee listed on the first page of the document.